

LexJet Premium Velvet WallPro™ SUV 20 oz.



LexJet Premium Velvet WallPro™ SUV 20 oz. is a bright-white, commercial grade wall covering designed for high-quality image reproduction on wide-format inkjet printers. The velvet texture features a finely embossed surface for reproducing high-resolution images. It is the most versatile of all the textures, and because it is certified Type II after printing with HP Gen3 inks, it is commonly used for murals found in sensitive environments such as healthcare facilities and schools, as well as corporate spaces, entertainment venues and retail.

- Bright-white base for expanded color gamut
- Commercial grade, Class A fire rating
- Meets Type II requirements after printing, passes with HP Gen3 inks
- Meets EPA requirements for low-VOC emitting products
- Compatible with all latex, eco-solvent, solvent and UV inks

Environmental Benefits

- Test results are representative of the media as supplied
- Meets or exceeds the following requirements of G.S.A. Federal Specification CCC-W-408D for Type II wallcovering: Washability, Scrubability, Abrasion Resistance, Breaking Strength, Stain Resistance, Tear Resistance, Blocking Resistance, Coating Adhesion, Cold Cracking, Heat Age, Shrinkage, Colorfastness to Light
- Class A fire rated when tested in accordance with ASTM E-84 Tunnel Test.
- Low-VOC emitting vinyl media meets California Department of Health Services section 01350 requirements for office and school interior
- Passes indoor air quality standard, CA 01350
- Free of phthalates, free of formaldehyde and heavy metal free

Product Highlights

Features	Benefits	Applications
<ul style="list-style-type: none">• 20 oz. commercial grade wallcovering with a smooth velvet texture• Bright-white color helps produce wide color gamut with improved highlight and shadow details• Compatible with all latex, eco-solvent, solvent and UV inks	<ul style="list-style-type: none">• Meets or exceeds all Federal Requirements of CCC-W-408D for Type II wallcoverings• Meets EPA requirements for low-VOC emitting products• Earned lowest mildew rating possible• Meets Type II, passes with HP Gen3 inks.	<ul style="list-style-type: none">• Corporate environment murals• Healthcare facilities• Schools, universities• Retail• Entertainment venues

Product Properties

Properties	Description
Unit	1 Roll
Core Size	3-in
Base Film	Brilliant-White PVC
Backing Fabric	Woven, poly-cotton backing
Emboss	Velvet
Total Weight	20 oz/linear yd or 13 oz/yd ²
Gauge	17 mil
Gloss Level	Matte 8-15
Printer/Ink Compatibility	Compatible with all Latex, Eco-Solvent, Solvent, and UV Inks
Imaging Side	Material is packaged with printable side facing in. Printable surface can be identified by the texture.
Finishing/Post Processing	Liquid top coatings can be used for added protection or desired finishes.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that are used and the environment where the print is displayed.
Optimal Print Environment	60° - 80° F, 50% Relative Humidity
Optimal Service Environment	-40° - 176° F (-40° C - 80° C)
Software Settings	Optimal printer settings will vary from printer manufacturer. For the best, and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and color matching software. Profiles are also available for download at http://www.lexjet.com/Profiles.aspx
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store vertically in original packaging. Unopened boxes should be stored horizontally to avoid telescoping of the material. Opened material should be tapped at leading edge to roll and stored horizontal on a media rack. If stored vertically, use of end cap is recommended to prevent contact with floor/shelf. If material is not stored in same area as printers, acclimate the material to environment 24 hours before printing.
Clean & Care	Easily cleaned using clear, warm water and mild soap with a natural sponge. For more difficult stains, the use of a stronger detergent may be tried. We recommend all cleaners first be tested to ensure compatibility with the wallcovering.
Shelf Life	1 year from the Lexjet ship date when stored in proper conditions.

Item Details

Size	SKU	UPC	Ordering
54in x 150ft	LJPWPROV54150		Buy Now

Product Performance & Suitability

Permeability: This product is intended for use in buildings designed and maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering so cleanable and durable also render it very low in permeability. Vinyl wallcovering products should not be installed on walls that contain excessive moisture or are subject to moisture infiltration (more permeable products should be considered for use under such conditions). If mold or mildew is present, or if walls show moisture damage or have excess moisture content, do not proceed with installation.