



Catena Series

Moderate production laminators

Designed to encapsulate and mount prints from color printers and copiers, the Catena Series provides a simple way to finish your full-color digital output. These models all feature heated rollers. The Catina 65 and 105 can also run pressure-sensitive films in addition to thermal films.

Catena 65 & 105

When productivity and profit count the most, the Catena 65 and 105 meet the requirements of your more demanding jobs. These larger units are able to handle a wider variety of applications including standard poster-sized prints.

Catena 35

This compact laminator is designed to provide safe and convenient thermal lamination in offices and small print shops.

Features and benefits

Easy to use

- LCD display indicates temperature, speed and Ready/Wait condition
- Silicone rubber rollers ensure timely clean-up
- Interlocking feed tray and magnetic safety shield provide safe operation
- For safety and savings, AUTO-OFF powers down unit after two hours of non-use
- The simple to use control panel allows the operator to make adjustments as needed for professionally laminated graphics

Versatile

- Designed for thermal (all models) and pressure-sensitive films (Catena 65 and 105)
- Roller gap adjustment handles mounting boards up to 3/16" thick
- Rewind shaft separates the pressure-sensitive release liner (Catena 65 and 105)

Quality

- Infrared heating coil distributes heat evenly and improves lamination quality
- Microprocessor controls temperature and guarantees fast response time
- Cooling fan ensures smooth, flat output
- Will not interfere with electrical surroundings; no buzzing, humming or flickering lights



Catena 105



Catena 65



Catena 35



Films and adhesives

For best results use high-quality GBC® films and mounting adhesives

- GBC Nap-Lam® II Thermal film
- Arctic® Pressure Sensitive film
- GBC Digital Polyester film
- Arctic Dura Mount adhesive
- Oactiva® thermal adhesive

Applications

- Placemats
- Posters
- Certificates
- POP displays

Specifications

| | |
|---------------------|--|
| Maximum film width: | |
| Catena 35 | 13" |
| Catena 65 | 25" |
| Catena 105 | 41" |
| Film gauge: | 1.5 to 10 mil |
| Core Diameter: | |
| Catena 35 | 1" (poly-in) |
| Catena 65 | 1" & 2.25" |
| Catena 105 | 2.25" (1" core adaptor also available) |
| Maximum Roll OD: | 5" outside diameter |
| Speed: | 1.5 fpm - 5 fpm |
| Dimensions: | |
| Catena 35 | 25" W x 13" H x 18" D |
| Catena 65 | 39" W x 17" H x 18" D |
| Catena 105 | 51" W x 48" H x 21" D |
| Weight: | |
| Catena 35 | 55 lbs. |
| Catena 65 | 84 lbs. |
| Catena 105 | 154 lbs. |
| Power: | |
| Catena 35 & 65 | 120V, 60Hz, 12 amp |
| Catena 105 | 220V, 50-60Hz, 15 amp |
| Safety: | CE, C/UL |



Call 800.723.4000 or visit us online at www.gbconnect.com to order or for more information.