






## The HP large format printing system—the complete solution

HP Latex printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



BMG trademark license code FSC®-C115319, see <u>fsc.org</u>. HP trademark license code FSC®-C017543, see <u>fsc.org</u>. Not all FSC®-certified products are available in all regions.

# Produce high quality with this resin-coated paper for high-volume production printing

#### Attain quality and economy in one photo paper

Ideal for production runs of photo enlargements, posters, and displays and designed for HP Latex printers, this resin-coated photo paper provides an economical price point without sacrificing quality.

#### Speed through production

Prints produced with HP Latex Inks come off the printer completely dry, helping you move high-volume projects through production quickly for on-time delivery to your customers.

#### Realize a broad color gamut for images that pop

With a wide color gamut and dynamic range on a bright-white base with a satin finish, this photo paper draws added attention to the image.

Target customers	Applications	Benefits
Point-of-purchase providers	Photo enlargements	Prints come out completely dry, enabling production printing
Trade show and exhibit companies	Point-of-purchase displays	Resin coating provides stability in production
Print service providers	Trade show and event displays	Bright-white surface, wide color gamut, satin finish
	Posters	FSC®-certified paper <sup>1</sup>

### **Technical specifications**



#### **HP Everyday Satin Photo Paper**

For the latest ICC profiles/paper presets and a variety of resources to help you get the most out of your printer and HP large format printing materials, please visit **globalBMG.com/hp**.

Weight	180 g/m² (48 lb) per ISO 536 Test Method					
Thickness	187 microns/7.4 mil per ISO 534 Test Method					
Opacity	Greater than 93% per TAPPI T-425 Test Method					
Brightness	96% per TAPPI T-452 Test Method					
Whiteness	130 per ISO 11475 Test Method					
Finish	Satin					
Operating temperature	15 to 35° C / 59 to 95° F					
Operating humidity	30 to 80% RH					
Dry time	Instant dry					
Shelf life	1 year, unopened in original packaging					
Storage temperature	0 to 40° C / 32 to 104° F					
Storage humidity	5 to 95% RH					
Country of origin	Product of Germany					
Ordering information	Product numbers	Roll sizes	UPC codes	Region		
	E4J38A	914 mm x 30,5 m (36 in x 100 ft)	848412014426	Worldwide		
	E4J39A	1067 mm x 30,5 m (42 in x 100 ft)	848412014433	Worldwide		
	E4J40A	1372 mm x 30,5 m (54 in x 100 ft)	848412014440	Worldwide		
	E4J41A	1524 mm x 30,5 m (60 in x 100 ft)	848412014457	Worldwide		
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warra statement, please see <b>globalBMG.com/hp/mediawarranties</b> .					



For detailed information on the HP large format printing materials portfolio and to order, see globalBMG.com/hp

