



11 mil Sunset Photo eSatin 300g

LexJet's new 11 mil Sunset Photo eSatin 300g paper answers photographers' requests for a heavier, more substantial photo paper, with excellent ink retention characteristics and a color gamut that is second to none. This paper maintains a traditional E surface finish, providing an elegant texture consistent to that of a dark room. This product solution is water and scratch-resistant, designed for the professional photographer. It's compatible with all leading dye- and pigment-based ink sets and performs exceptionally well with all Epson and Canon printers. All rolls require a 3" core (or core adapter).

Property	Specifications
Material	Resin-coated (RC) photo paper
Gauge	11 mil
Basis Weight	300 g/m ²
CIE Whiteness	110
ISO Brightness	95
Gloss at 60°	15 +/- 5
Surface finish	E Surface
Printer/Ink Compatibility	Universally compatible with all leading dye- and pigment-based inkjet photo printers. Performs exceptionally well on all Epson and Canon printers.
Imaging Side	Material is packaged with printable side facing up. Printable surface can be identified by a slight tackiness.
Software Settings	The coating on this product is engineered for better than 300% ink coverage. A photo luster, satin, or semi-gloss setting is the recommended starting point, however, we recommend a custom ICC profile for optimal results. Please refer to www.lexjet.com , for starting point ICC profiles for some printers.
Finishing/Post Processing	For image stability and permanence it is always recommended that you protect the printed side. This can be done by mounting under glass, clear coating, photographic sleeves or laminating. Pressure sensitive laminates will give you the best bond. Hand applying the laminate is not recommended.
Optimal Service Environment	72° F, 50% R.H.
Handling Recommendations	Due to the absorptive nature of the coating, you should avoid touching the coated surface of the paper. It's always recommended that cotton gloves be used when handling ink jet coated materials.
Ideal Storage Conditions	70°F (21°C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	Greater than 1 year from LexJet ship date when stored in proper conditions.

Product Performance & Suitability: All of the descriptive information and recommendations for the use of LexJet products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by LexJet. All purchasers of LexJet products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.