

LexJet Production Display Film



LexJet Production Display Film is designed for the quick and easy printing for all kinds of display graphics, including trade show graphics, banner stands and point-of-purchase displays. The matte surface is scratch- and water-resistant, and produces exceptional image quality.

It is an economical choice for lay-flat trade show and point-of-purchase graphics that will be mounted on pop-up and retractable display systems. Compatible with water-based UV pigment and latex inks, this opaque film hides the display hardware.

Product Highlights

Features	Strengths	Applications
Water-resistant and scratch-resistant without lamination	Economical choice	A perfect solution for lay-flat trade show graphics
Lay-flat, dimensionally stable film	Smooth, matte surface for optimal viewing conditions	Ideal for retractable banner stand graphics
99% opaque	Hides display hardware	POP graphics
		Hanging displays

Product Properties

Properties	Description
Unit	1 Roll
Core Size	3in Core
Base Film	PP+PET+PP lay flat film
Finish	Smooth, Matte
Weight	235 gsm
Thickness	10 mils / 250 micron
Opacity	99%
Printer/Ink Compatibility	Compatible with water based UV pigmented ink and Latex ink
Optimal Print Environment	15-30° C, 30-50% R.H.
Ideal Storage Conditions	10-25° C, 20% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the LexJet ship date when stored in proper conditions.

Note:

The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire cognitions. Consult an architect or fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.

Item Details

Size	SKU	UPC	Ordering
36in x 20ft	PDF36T		
36in x 100ft	PDF3600		
50in x 100ft	PDF5000		
60in x 100ft	PDF6000		