

## LexJet Production Display Film SUV



LexJet Production Display Film SUV is designed for the quick and easy production of all kinds of display graphics, including trade show graphics, banner stands and point-of-purchase displays. The semi-matte surface is scratch- and water-resistant, and produces exceptional image quality.

The base material is stable, durable and will not curl so that it stays flat when unrolled for display. Compatible with solvent, low-solvent, UV-curable and latex inks, LexJet Production Display Film SUV does not need to be laminated: Just print, trim and ship.

### Product Highlights

Features	Strengths	Applications
Water-resistant and scratch-resistant without lamination	Economical choice	A perfect solution for lay-flat trade show graphics
Lay-flat, dimensionally stable film	Smooth, semi-matte surface for optimal viewing conditions	Ideal for retractable banner stand graphics
Exceptional image quality	99% opacity for blackout use	Hanging signage
Fast dry times	Perfect for high-production environments	POP displays

## Product Properties

Properties	Description
Unit	1 Roll
Core Size	3in Core
Base Film	PP+PET+PP lay flat film
Finish	Smooth, Semi-Matte
Weight	240 gsm
Thickness	10 mils / 250 micron
Opacity	99%
Printer/Ink Compatibility	Compatible with Eco-Solvent, Latex and UV Curable Ink.
Optimal Print Environment	15-30° C, 30-50% R.H.
Ideal Storage Conditions	10-25° C, 20% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the LexJet ship date when stored in proper conditions.

**Note:**

The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire cognitions. Consult an architect or fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.

## Item Details

Size	SKU	UPC	Ordering
36in x 20ft	PDFS36T		
36in x 100ft	PDFS3600		
54in x 100ft	PDFS5400		
60in x 100ft	PDFS6000		