

AN EARTH INTELLIGENT WALLCOVERING

NO PVC, NO PLASTICIZERS, NO PHTHALATES

NO CHLORINE, NO HEAVY METALS, NO FORMALDEHYDE

31% POST CONSUMER RECYCLED (highest in the industry)

CLASS "A" FIRE RATING: TYPE II COMMERCIAL STRENGTH

LEED CREDITS (contributes to 2 LEED credits and conditionally 4 others)

EXTREMELY LOW VOC'S (passed CA-1350 Indoor Air Quality)

RECYCLABLE

Introducing **terralon**, an earth intelligent wallcovering media developed by DreamScape for solvent, eco-solvent, UV curable, and latex inkjet printers. Finally a product that prints and functions as uniformly as vinyl, while answering the demands of an ecologically conscious society.



FOR MORE INFORMATION GO TO: WWW.DREAMSCAPEWALLS.COM OR CALL: (973)-625-5570

Terralon™ Specification Sheet

v:011110



Product Name: Terralon™ by DreamScape

Description: PVC Free Eco-friendly digitally printable wallcovering, Type II 54", 31% post consumer recycled content, for UV curable +

Solvent + Eco Solvent inkjet printers

Construction: 100% Terralon™ (Proprietary Polyester/Natural Fiber Technology)

Weight: 14oz PLY / 435.2 G/PLM 9.3oz PSY / 315.3 G/PSM

Availability: Roll sizes: 54"x25yds, 54"x50yds, 54"x100yds Trial Rolls (27"x15')

Packaging: 3" core, wound print side out, wrapped in black back, Shipped in heavy duty cardboard tube

Application: Standard commercial wallcovering pastes/primers and techniques

Physicals: Meets or exceeds federal specification CCCW-408D for Type II wallcoverings

Environmental: PVC & POA (Olefin) Free, No Plasticizers, No Phthalates, No Formaldehyde, No Chlorine, No Halogen, No

Heavy Metals, including: Cadmium, Mercury, Lead, or Zinc, and No Ozone Depleting Chemicals.

Minimum of 31% post-consumer recycled content

Recyclable*

Breathable** -very high permeability rating of 66 Perms based on ASTM E96 dry cup method

Made with 100% water based adhesive systems

No harmful off gassing

Low Voc emitting

Air Quality: Meets California Section IAQ 1350—Third party certified by Berkeley Analytical Associates

Flame and Smoke: Class "A" Fire Rated – tested in accordance with ASTM-E84 Tunnel Test

NFPA-101 (passed)

LEEDS Eligibility: Terralon™ can contribute towards the earning of 2 LEEDs credits and, conditionally, 2 others-

MR Credit 4.1 Recycled content 20% MR Credit 4.2 Recycled content 30%

Conditionally-

MR Credit 2.1 Contribution to project recycling program
MR Credit 2.2 Contribution to project recycling program
MR Credit 5.1 Manufactured local to the new construction
EQ Credit 4.1 When mounted with use of low emitting adhesives

Warranty: 5 Year Warranty against manufacturing defects. Additional information regarding warranty is available on our website at

http://www.dreamscapewalls.com/

Comments: *All Terralon™ wallcoverings are recyclable. Construction waste and after use material can be returned to

Roysons for recycling back into wallcovering and other industrial products as part of the Roysons Reclamation

Program. For details visit http://www.roysons.com/

**Permeable surface allows transfer of moisture to minimize possibility of mold and mildew growth.

Terralon™ is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation, and/or accumulation at wall cavities and wall surfaces, especially in warm, humid climates. Dry cup tests performed by VARTEST company.