

dreamscape

Product Packaging

Each roll is meticulously packaged in a re-usable suspension box or ultra sturdy tube. **(No flat spots, no creases, no splices)**

STD Lengths: 75', 150', 300'

STD Widths: 30", 48", 54", 60", 75" (+/- 1/8")

Core Diameter: 3 inches i.d. Heavy-Duty

*Custom lengths and widths available on request

Physical Properties

Product Weight: 200z. per lineal yd., (130z. per sq. yd.)

Vinyl Weight: 170z. per lineal yd.

Fabric Weight: 30z. per lineal yd.

Thickness: 0.015 to 0.030 in.

*depending on texture

Fabric: Poly-Cotton Osnaburg or Polyester Nonwoven

*depending on texture

Breaking Strengths, lbs. force

Machine Direction-warp:

*Exceeds Type II minimum of 50lbs.

Cross Machine Direction-fill:

*Exceeds Type II minimum of 55lbs.

Tearing Strength, Scale

Machine Direction-warp:

*Exceeds Type II minimum of 25lbs.

Cross Machine Direction-fill:

*Exceeds Type II minimum of 25lbs

Cold Crack Resistance @ 20° F

No Change

Heat Aging (7 days at 158° F)

*Does not become stiff, brittle, discolored, or show loss of grain

Specifications/ Testing/ Certification

Federal Specification:

*CCC-408-D,C,B,A *Type II *Class A

CFFA Specification:

*CFFA-W-101-D *Type II *Class A

Fire Testing

ASTM-E84 Tunnel Test Class A

NFPA286 Corner Burn Test Class A

NFPA265 Corner Burn Test Class A

BS476 Part 6&7

*Meets or exceeds requirements for flame spread, smoke developments and flashover.

Mold/Mildew/ Bacterial Resistance

ASTM-G21 Specifications: Passed all requirements of CCCW-408-D

Environment

NYC MEA: Registered

*Cadmium and Lead Free Formulation



dream it...print it...hang it...
dream it...print it...hang it...