

LexJet Premium Smooth Pearl WallPro™ SUV 20 oz.



LexJet Premium Smooth Pearl WallPro™ SUV 20 oz. features an un-embossed pearl ground with a satin sheen that provides an elegant surface for reproducing high-resolution images. This commercial grade wall covering is designed for high-quality image reproduction on wide-format inkjet printers. This low-VOC-emitting vinyl is Class A fire rating, making it an environmentally conscious choice for corporate, healthcare, entertainment and retail wall murals.

- Smooth pearl base with a satin finish
- Commercial grade, Class A fire rating
- Meets EPA requirements for low-VOC emitting products
- Compatible with all latex, eco-solvent, solvent and UV inks

Environmental Benefits

- Test results are representative of the media as supplied
- Meets or exceeds the following requirements of G.S.A. Federal Specification CCC-W-408D for Type II wallcovering: Washability, Scrubability, Abrasion Resistance, Breaking Strength, Stain Resistance, Tear Resistance, Blocking Resistance, Coating Adhesion, Cold Cracking, Heat Age, Shrinkage, Colorfastness to Light
- Class A fire rated when tested in accordance with ASTM E-84 Tunnel Test.
- Low-VOC emitting vinyl media meets California Department of Health Services section 01350 requirements for office and school interior
- Can contribute to LEED for low-emitting materials and recycled content
- Warranty: 5-year limited warranty against manufacturing defects

Product Highlights

| Features | Benefits | Applications |
|---|---|--|
| <ul style="list-style-type: none">• 20 oz. commercial grade wallcovering with a smooth pearl finish• Smooth pearl finish offers an elegant surface for high-resolution décor• Compatible with all latex, eco-solvent, solvent and UV inks | <ul style="list-style-type: none">• Meets or exceeds all Federal Requirements of CCC-W-408D for Type II wallcoverings• Meets EPA requirements for low-VOC emitting products• Earned lowest mildew rating possible | <ul style="list-style-type: none">• Corporate environment murals• Healthcare facilities• Retail• Entertainment venues |

Product Properties

| Properties | Description |
|-----------------------------|---|
| Unit | 1 Roll |
| Core Size | 3-in |
| Base Film | Vinyl |
| Backing Fabric | Non-woven |
| Backing Weight | 1.8 oz/yd ² |
| Emboss | None |
| Total Weight | 20 oz/linear yd or 13 oz/yd ² |
| Gauge | 16 mil |
| Gloss Level | Matte 8-15 |
| Printer/Ink Compatibility | Compatible with all Latex, Eco-Solvent, Solvent, and UV Inks |
| Imaging Side | Material is packaged with printable side facing in. Printable surface can be identified by the texture. |
| Finishing/Post Processing | Liquid top coatings can be used for added protection or desired finishes. To achieve Type II results, product must be paired with Marabu ClearShield Wall Armor. |
| Light Fastness | The fading time of inkjet ink is a direct result of the inks that are used and the environment where the print is displayed. |
| Optimal Print Environment | 60° - 80° F, 50% Relative Humidity |
| Optimal Service Environment | -40° - 176° F (-40° C - 80° C) |
| Software Settings | Optimal printer settings will vary from printer manufacturer. For the best, and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and color matching software. Profiles are also available for download at http://www.lexjet.com/Profiles.aspx |
| Ideal Storage Conditions | 70° F (21° C), 50% R.H. (a controlled environment is recommended); store vertically in original packaging. |
| Clean & Care | Easily cleaned using clear, warm water and mild soap with a natural sponge. For more difficult stains, the use of a stronger detergent may be tried. We recommend all cleaners first be tested to ensure compatibility with the wallcovering. |

Item Details

| Size | SKU | UPC | Ordering |
|--------------|--------------|-----|-------------------------|
| 54in x 30ft | LJPWPSP5430 | | Buy Now |
| 54in x 150ft | LJPWPSP54150 | | Buy Now |

Product Performance & Suitability

Permeability: This product is intended for use in buildings designed and maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering so cleanable and durable also render it very low in permeability. Vinyl wallcovering products should not be installed on walls that contain excessive moisture or are subject to moisture infiltration (more permeable products should be considered for use under such conditions). If mold or mildew is present, or if walls show moisture damage or have excess moisture content, do not proceed with installation.