

LexJet Premium Gold Mylar WallPro™



LexJet Gold Mylar WallPro™ has a fine canvas emboss with a metallic finish that provides an excellent surface for reproducing high-resolution images without the need for metallic inks. This commercial grade wall covering designed for high-quality image reproduction on wide-format inkjet printers. This wallcovering offers an eye-catching base for murals found in corporate environments, healthcare facilities, entertainment venues and retail spaces.

- Gold Mylar base with a metallic finish
- Commercial grade, Class A fire rating
- Meets EPA requirements for low-VOC emitting products
- Compatible with all latex and UV inks

Environmental Benefits

- Test results are representative of the media as supplied
- Meets or exceeds the following requirements of G.S.A. Federal Specification CCC-W-408D for Type II wallcovering: Washability, Scrubability, Abrasion Resistance, Breaking Strength, Stain Resistance, Tear Resistance, Blocking Resistance, Coating Adhesion, Cold Cracking, Heat Age, Shrinkage, Colorfastness to Light
- Class A fire rated when tested in accordance with ASTM E-84 Tunnel Test.
- Low-VOC emitting vinyl media meets California Department of Health Services section 01350 requirements for office and school interior
- Can contribute to LEED for low-emitting materials and recycled content
- Warranty: 5-year limited warranty against manufacturing defects

Product Highlights

Features	Benefits	Applications
<ul style="list-style-type: none"> • Commercial grade wallcovering with a metallic gold fine canvas embossed texture • Gold metallic finish provides excellent surface to produce high-quality designs without the need for metallic inks • Compatible with all latex and UV inks 	<ul style="list-style-type: none"> • Meets or exceeds all Federal Requirements of CCC-W-408D for Type II wallcoverings • Meets EPA requirements for low-VOC emitting products • Earned lowest mildew rating possible 	<ul style="list-style-type: none"> • Corporate environment murals • Healthcare facilities • Retail • Entertainment venues

Product Properties

Properties	Description
Unit	1 Roll
Core Size	3-in
Base Film	Vinyl
Backing Fabric	Non-woven
Backing Weight	1.8 oz/yd ²
Emboss	Fine Canvas
Total Weight	23 oz/linear yd
Gauge	18 mil
Printer/Ink Compatibility	Compatible with all Latex and UV Inks
Imaging Side	Material is packaged with printable side facing in. Printable surface can be identified by the texture.
Finishing/Post Processing	Liquid top coatings can be used for added protection or desired finishes. To achieve Type II results, product must be paired with Marabu ClearShield Wall Armor.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that are used and the environment where the print is displayed.
Optimal Print Environment	60° - 80° F, 50% Relative Humidity
Optimal Service Environment	-40° - 176° F (-40° C - 80° C)
Software Settings	Optimal printer settings will vary from printer manufacturer. For the best, and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and color matching software. Profiles are also available for download at http://www.lexjet.com/Profiles.aspx
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store vertically in original packaging.
Clean & Care	Easily cleaned using clear, warm water and mild soap with a natural sponge. For more difficult stains, the use of a stronger detergent may be tried. We recommend all cleaners first be tested to ensure compatibility with the wallcovering.
Shelf Life	1 year from the Lexjet ship date when stored in proper conditions.

Item Details

Size	SKU	UPC	Ordering
54in x 30ft	LJPGMWP5430		Coming Soon
54in x 150ft	LJPGMWP54150		Coming Soon

Product Performance & Suitability

Permeability: This product is intended for use in buildings designed and maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering so cleanable and durable also render it very low in permeability. Vinyl wallcovering products should not be installed on walls that contain excessive moisture or are subject to moisture infiltration (more permeable products should be considered for use under such conditions). If mold or mildew is present, or if walls show moisture damage or have excess moisture content, do not proceed with installation.