

LexJet InFuze™ Rigid Substrate Dye Sublimation Paper

Optimized for ChromaLuxe® Panels



LexJet InFuze™ Rigid Substrate Dye-Sublimation Paper is a medium-weight, 120 gsm, water-based sublimation transfer paper with high ink transferability. The proprietary microporous ink-receptive coating is applied to a low-cockle, layflat base producing fast dry, full-color graphics optimized for transferring onto ChromaLuxe(R) panels. For medium-to-high ink coverage and applications such as wall art, table tops, high-end photo-art.

Product Highlights

Features	Strengths	Applications
120 gsm base and microporous inkjet coating	Optimized for ChromaLuxe(R) panels	Wall art, table tops, high-end photo art
Low ink penetration into base	Higher percentage of ink transfer	Images with high color saturation
Microporous ink-receptive coating	Rapid ink drying; shorter wait time to transfer	High-resolution rigid panels
High value	Economical transfer sheet	Competitive bids, budget beaters
	Lower overall cost of finished piece	

Product Properties

Properties	Description
Core Size	3 in
Base	Sublimation Paper
Coating	Microporous
Weight	120 gsm
Thickness	5.9 mil
Printer/Ink Compatibility	Water-based sublimation inks
Imaging Side	Material is packaged with printable side facing up
Finishing/Post Processing	Specifically designed for sublimation transfer onto ChromaLuxe® Panels
Optimal Environment	68 ° to 77 °F (20 ° to 25 °C) 40 - 60% RH It is recommended to adapt the material to indoor print environment at least 24 hours before usage
Ideal Storage Conditions	Protect material from direct sunlight or moisture. Store in original packaging under normal climate conditions of 23°C, 50 % RH
Shelf Life	1 year from the LexJet ship date when stored in proper conditions

Item Details

Size	SKU
17in x 250ft	INFUZERG17250
24in x 250ft	INFUZERG24250
25in x 250ft	INFUZERG25250
36in x 250ft	INFUZERG36250
37in x 250ft	INFUZERG37250
44in x 250ft	INFUZERG44250
64in x 360ft	INFUZERG64360

Product Performance & Suitability

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH).

Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.