

LexJet FlexTek 200g SUV



LexJet FlexTek 200 SUV is a PVC-free, multi-functional non-woven technical fabric that can be used in a wide range of indoor and outdoor applications. The base is 100% non-woven polyester with an embossed texture that looks and feels like a woven fabric. Great tear strength and woven pattern surface texture make this versatile product a good choice for wall art, signs and banners where durability and flexibility are paramount. Compatible with all eco-solvent, latex and UV-curable inks.

Product Highlights

Features	Strengths	Applications
PVC-free	Recyclable, reliable print performance over time and wide range of temperatures. Great shelf-life.	Wider range of post-use options.
FLEXible range of applications	Versatile, multi-functional material. Less inventory.	Wall art, banner, gallery wraps
Cost effective option	The non-woven polyester base has advantages over woven, extruded or calendared alternatives.	Compare performance to canvas, fabric or alternative banner materials. Budget beater.
Tear-resistant	Polyester non-woven technical fabric base provides stability and strength (wet or dry) for grommets, stitching, wrapping and folding.	Grommetable, stitchable. Indoor or outdoor signage, banners.
Embossed textured surface	Textured look of a woven surface with bi-axial strength of a true non-woven base.	Images look great with close or long distance viewing.

Product Properties

Properties	Description
Unit	1 Roll
Core Size	3in
Base Material	Non-woven Polyester
Surface Finish	Semi-Matte
Gauge	11 mil
Basis Weight	200 gsm
Whiteness (W-E313)	136.14
Brightness (TB-452)	95
Gloss Level (60°)	5.9
Opacity	94.4%
Printer/Ink Compatibility	Compatible with all Eco-Solvent, Latex and UV Curable inks
Imaging Side	Material is packaged with printable side facing up
Optimal Environment	68 ° to 77 ° F (20 ° to 25 ° C) 40 - 60% RH It is recommended to adapt the material to indoor print environment at least 24 hours before usage
Ideal Storage Conditions	Protect material from direct sunlight or moisture. Store in original packaging under normal climate conditions of 23°C, 50 % RH
Shelf Life	1 year from the LexJet ship date when stored in proper conditions

Item Details

Size	SKU	UPC	Ordering
36in x 150ft	FLEXSUV36150	848412022940	Add to Cart
54in x 150ft	FLEXSUV54150	848412022957	Add to Cart
60in x 150ft	FLEXSUV60150	848412022964	Add to Cart

Product Performance & Suitability

All of the descriptive information and recommendations for the use of LexJet products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by LexJet. All purchasers of LexJet products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (Including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.