

Sunset Production Satin Canvas SUV



LexJet Sunset Production Satin Canvas SUV is the 100% polyester option for quality canvas prints in high-production environments. This U.S.-made product is a more cost-effective alternative to poly-cotton blends at the lowest price point in its class. Yet, it still has a high-end feel with the look of a traditional 2-over-1 poly-cotton weave, with no optical brighteners.

This canvas performs well on all solvent, eco-solvent, latex and UV-curable printers, making it a highly versatile product that delivers consistent results for busy print shops and studios. It's also ideal for canvas wraps, with no cracking over stretcher bars.

Product Highlights

Features	Strengths	Applications
Domestically produced; MADE IN THE USA!	Provides product consistency makes it the ideal choice for canvas prints	High-production canvas prints
A satin, bright-white, OBA-free 100% polyester canvas	Largest color gamut of competing polyester canvas materials	
Finished look and feel of a traditional 2-over-1 weave		

Product Properties

Properties	Description
Unit	1 Roll
Roll Size	3in Core
Base Film	100% Polyester
Gloss Level (60)	Satin (5)
Thickness	14 mil
Total Weight	342 gsm
Basis Weight	320g
Whiteness	86.82 CIE
Brightness	89.63
Opacity	99.3%
pH Value	7.5-9.5
Printer/Ink Compatibility	Optimized for use on all solvent, eco-solvent, latex, and UV-curable inks.
Color Matching	For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and/or color matching software.
Imaging Side	Roll Out
Finishing/Post Processing	No post processing or finishing is required on this paper. However, a clear fixative may be applied to enhance certain areas of the print.
Light Fastness	The fading time of inkjet ink is a direct result of the inks you choose, as well as the environment where the print is displayed. Contact the ink manufacturer to determine a specific ink's suitability for a particular application.
Optimal Print Environment	68-77° F , 20-60% R.H. For end use: 0-300° F
Handling Recommendations	Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials. Rolls of LexJet Sunset media are supplied with the coated side facing out.
Software Settings	The coating on this product is engineered for better than 300% ink coverage. Any canvas fabric setting is the appropriate starting point. However, we recommend that you try different settings to achieve optimum performance for your specific application.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the LexJet ship date when stored in proper conditions.

Note:

The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire cognitions. Consult an architect or fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.

Item Details

Size	SKU	UPC	Ordering
54in x 150ft	SPSC54150	00848412019902	
60in x 150ft	SPSC60150	00848412019919	