

LexJet Solvent Print-N-Stick Fabric



LexJet Solvent Print-N-Stick Fabric delivers superior image quality with one of the most versatile products LexJet has to offer. This tightly woven fabric, with a smooth finish and a satin sheen, delivers the most vivid colors compared to other fabrics in the market. The self-adhesive fabric is bright-white, 7 mil, 100 percent polyester base with a repositionable adhesive that removes cleanly and easily with no residue. The printable fabric is designed for effortless application to a wide range of flat surfaces and it will not rip, wrinkle or stretch in production making it easy to contour cut into any shape. The fabric also provides a higher opacity than competing products, making it perfect for tiling images. Application ideas include wall cut-outs, wall murals, decals, signs, window graphics and more.

- Easy to print, install, reposition and remove
- Smoother weave provides detail photographic image quality with vivid colors
- Bright white, 7 mil, 100% polyester satin sheen
- 94% opacity level
- Perfect for wall graphics, contoured cutouts and point-of-purchase displays
- Compatible with latex, eco-solvent and solvent inks

Product Highlights

Features	Strengths	Applications
Bright white, 7 mil, 100% polyester satin sheen	Easy to print, install, reposition and remove	Temporary applications, graphics and decals
Smoother weave provides detail photographic image quality with vivid colors	Will not rip, wrinkle or stretch	Signs, window graphics
Satin sheen which offers POP to graphics	Can be contour cut into any shape	Perfect for wall graphics, contoured cutouts and point-of-purchase displays
Class A, ASTM E84 Fire Rating		

Product Properties

Properties	Description
Unit	1 Roll
Core Size	3in Core
Material	White Polyester Fabric
Gauge	7 mil (Fabric) 5 mil (Liner)
Weight	347 gsm
Thickness	7 mil
Finish	Satin
Brightness	93.14
Whiteness	104.85
Opacity	94
Finishing	No post processing or finishing is required on this fabric
Operating Temperature	70° F (21° C)
Operating Humidity	50% R.H.
Adhesive Type	Acrylic, removable pressure sensitive adhesive
Gloss Level	9.7
Shelf Life	1 year from the LexJet ship date when stored in proper conditions
Storage Temperature	70° F (21° C) (a controlled environment is recommended); store in original packaging
Storage Humidity	50% R.H. (a controlled environment is recommended); store in original packaging
Liner	70# stay flat liner
Ink Compatibility	Compatible with all inkjet printers using eco solvent, solvent and UV-curable ink
RIP & Printer Media Settings	For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and color matching software. However, if these tools are not available use one of the onboard media settings for cast vinyl
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light fastness data
Optimal Service Environment	70° F (21° C), 50% R.H.

Note:

The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire cognitions. Consult an architect or fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.

Item Details

Size	SKU	UPC
27in x 20ft	SPNS2720	848412016925
42in x 150ft	SPNS42	848412016932
54in x 150ft	SPNS54	848412016949
60in x 150ft	SPNS60	848412016956

Product Performance & Suitability

All of the descriptive information and recommendations for the use of LexJet products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by LexJet. All purchasers of LexJet products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (Including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.