



## TECHNICAL DATA SHEET

### GF 1701 PRIMARY FLAG (FR)

**WEIGHT:** 3.4 oz/yd<sup>2</sup> (114 g/m<sup>2</sup>)

**COMPOSITION:** 100% Polyester

**WIDTH:** 61"

**CONSTRUCTION:** Knit

**PRINTING COMPATIBILITY:** Dye Sublimation Printing

**FLAME RETARDANCY:** NFPA-701; DIN-4102 B1; California Administrative Code Title 19 -  
Public Safety, Section 1237

**TRANSFER CONDITIONS:**

385-390°F

25 P.S.I.

30 Seconds

**DURABILITY:** Dependent upon the environment the fabric is exposed to.

**SUGGESTED APPLICATIONS:** Flags

The above recommendations are a result of laboratory testing. We recommend additional testing in the manufacturing facility prior to printing. Data are averages achieved for actual production runs. Product safety evaluations may not have been completed for the intended use. Samples of this product should be used for concept evaluations only.

Revised: 3.1.2019

FISHER TEXTILES | 139 Business Park Drive, Indian Trail, NC 28079

Toll Free: 800.554.8886 | Fax: 704.821.8880 | [www.fishertextiles.com](http://www.fishertextiles.com) | 