

TECHNICAL DATA SHEET

GF 1708 HEAVY KNIT (FR)

WEIGHT: 6.8 oz/yd² (230 g/m²)

COMPOSITION:

100% Polyester

WIDTH:

61"

CONSTRUCTION:

Warp Knit

PRINTING COMPATIBILITY:

Dye Sublimation Printing

FLAME RETARDANCY:

German B-1 DIN 4102-1; NFPA 701; California Administrative Code Title 19 - Public Safety, Section 1237

TRANSFER CONDITIONS:

385-400°F

35 P.S.I.

35 Seconds

THICKNESS:

0.49 mm

SPECIAL FEATURES:

Tight structure, high opacity, soft, smooth, bright glossy print side, excellent durability

DURABILITY:

Dependent upon the environment the fabric is exposed to.

SUGGESTED APPLICATIONS:

Banners - Indoor, Exhibit Graphics, Home Furnishings, Photographic Back Drops, Retail Displays, Roll Up Banner Stands, Silicone Edge Graphics

The above recommendations are a result of laboratory testing. We recommend additional testing in the manufacturing facility prior to printing. Data are averages achieved for actual production runs. Product safety evaluations may not have been completed for the intended use. Samples of this product should be used for concept evaluations only.

Revised: 1.2.2019