



TECHNICAL DATA SHEET

GF 1707 SOFT KNIT (FR)

WEIGHT: 5.1 oz/yd² (170 g/m²)

COMPOSITION: 100% Polyester

WIDTH: 61"

CONSTRUCTION: Warp Knit

PRINTING COMPATIBILITY: Dye Sublimation Printing

FLAME RETARDANCY:

German B-1 DIN 4102-1; NFPA 701; California Administrative Code
Title 19 - Public Safety, Section 1237

TRANSFER CONDITIONS:

385-400°F
35 P.S.I.
30 Seconds

THICKNESS: 0.54 mm

STRETCH: Length: 17.5% Width: 3.75%

SPECIAL FEATURES: Tight structure and high opacity, excellent durability and tear strength

DURABILITY: Dependent upon the environment the fabric is exposed to.

SUGGESTED APPLICATIONS:

Banners - Indoor, Exhibit Graphics, Home Furnishings,
Photographic Back Drops, Retail Displays, Silicone Edge
Graphics, Table Covers

The above recommendations are a result of laboratory testing. We recommend additional testing in the manufacturing facility prior to printing. Data are averages achieved for actual production runs. Product safety evaluations may not have been completed for the intended use. Samples of this product should be used for concept evaluations only.

Revised: 1.2.2019

FISHER TEXTILES | 139 Business Park Drive, Indian Trail, NC 28079

Toll Free: 800.554.8886 | Fax: 704.821.8880 | www.fishertextiles.com | 