



TECHNICAL DATA SHEET

GF 9048 EZ STRETCH® PREMIUM (FR)

WEIGHT: 8.0 oz/yd² (269 g/m²)

COMPOSITION: 100% Polyester

WIDTH: 61"

CONSTRUCTION: Knit

PRINTING COMPATIBILITY: Dye Sublimation and Latex Printing

FLAME RETARDANCY:

NFPA-701; California Administrative Code Title 19 - Public Safety,
Section 1237

TRANSFER CONDITIONS:

395-400°F
35 P.S.I.
40 Seconds

STRETCH:

Length: 12.5% Width: 25%

CARE INSTRUCTIONS:

Wash with cold water and mild soap and tumble dry under low heat.

DURABILITY:

Dependent upon the environment the fabric is exposed to.

SUGGESTED APPLICATIONS:

Exhibit Graphics, Geometric/Stretch Displays, Photographic
Back Drops, Silicone Edge Graphics, Tension Displays

NOTE:

This style has stretch and width may vary from listed.

The above recommendations are a result of laboratory testing. We recommend additional testing in the manufacturing facility prior to printing. Data are averages achieved for actual production runs. Product safety evaluations may not have been completed for the intended use. Samples of this product should be used for concept evaluations only.

Revised: 3.1.2019

FISHER TEXTILES | 139 Business Park Drive, Indian Trail, NC 28079

Toll Free: 800.554.8886 | Fax: 704.821.8880 | www.fishertextiles.com |