



## TECHNICAL DATA SHEET

GF 4608 POWER STRETCH (FR)

**WEIGHT:** 7.3 oz/yd<sup>2</sup> (246 g/m<sup>2</sup>)

**COMPOSITION:** 100% Polyester

**WIDTH:** 61"

**CONSTRUCTION:** Warp Knit

**PRINTING COMPATIBILITY:** Dye Sublimation Printing

**FLAME RETARDANCY:** NFPA-701

**TRANSFER CONDITIONS:**

395-400°F

35 P.S.I.

40 Seconds

**STRETCH:** Width: 14% ± 5% Length: 57% ± 5%

**CARE INSTRUCTIONS:**

Washing of this fabric should be with cold water and mild soap and tumble dry under low heat.

**DURABILITY:**

Dependent upon the environment the fabric is exposed to.

**SUGGESTED APPLICATIONS:**

Architectural, Geometric/Stretch Displays, Photographic Back Drops, Silicone Edge Graphics, Tension Displays

**NOTE:**

This style has stretch and width may vary from listed.

The above recommendations are a result of laboratory testing. We recommend additional testing in the manufacturing facility prior to printing. Data are averages achieved for actual production runs. Product safety evaluations may not have been completed for the intended use. Samples of this product should be used for concept evaluations only.

Revised: 5.30.2018

FISHER TEXTILES | 139 Business Park Drive, Indian Trail, NC 28079

Toll Free: 800.554.8886 | Fax: 704.821.8880 | [www.fishertextiles.com](http://www.fishertextiles.com) |