




HP Super Heavyweight Plus Matte Paper



The HP DesignJet printing system—the complete solution

HP DesignJet printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



Produce professional full-color graphics

See highly saturated images that lie flat, smooth

When the job requires professional full-color graphics and photo-realistic images this heavy, matte-finish paper—with a barrier layer under a thick top coating that enables ripple-free prints—delivers excellent highlights and rich shadow details.

Streamline your workflow

Move quickly and smoothly through post-print processing. Instant-dry, smear-resistant prints—even with high ink densities—enable immediate handling and lamination. Excellent film laminate compatibility helps you keep peak productivity.

Create durable prints for a versatile set of jobs

Produce a wide array of graphics-display applications and print with both Original HP dye- and pigment-based inks.

Target customers	Applications	Benefits
Print service providers	Trade show and event displays	Highly-saturated, photo-realistic images
Large retailers	Posters and presentations	Bright white, smooth coating for vivid color contrast
Graphic designers	POP and retail displays	Flat, smooth prints even under high ink densities
Ad agencies	Geographic Information Systems (GIS)	Excellent film laminate compatibility
Repro houses	Architecture (AEC)	Instant-dry, smear-resistant prints
Geographic Information Systems (GIS) professionals	Engineering (CAD)	Compatible with both Original HP dye- and pigment-based inks
Architects		

Technical specifications



HP Super Heavyweight Plus Matte Paper

For the latest ICC profiles/paper presets and a variety of resources to help you get the most out of your printer and HP large format printing materials, please visit HPLFMedia.com/paperpresets..

Weight (without liner)	200 g/m ² per ISO 536 Test Method, (55 lbs)			
Thickness	264 microns /10.4 mil per ISO 534 Test Method			
Opacity	98% per TAPPI T-425 Test Method			
Brightness	Greater than 94% per TAPPI T-452 Test Method			
Whiteness	Greater than 124 per CIE Ganz 82 Test Method			
Finish	Matte			
Operating temperature	15 to 35° C / 59 to 95° F			
Operating humidity	20 to 80% RH			
Dry time	Instant dry (at 23° C, 50% RH)			
Lamination	Yes, compatible with thermal, heat assist, and pressure-sensitive film laminates			
Shelf life	1 year, unopened in original packaging			
Storage temperature	0 to 40° C / 32 to 104° F			
Storage humidity	5 to 95% RH			
Recyclability	Recyclable through commonly available recycling programs ¹			
Country of origin	Product of France			
Ordering information	Product numbers	Roll sizes	UPC codes	Region
	Q6626B	610 mm x 30,5 m (24 in x 100 ft)	848412013566	Worldwide
	Q6627B	914 mm x 30,5 m (36 in x 100 ft)	848412013573	Worldwide
	Q6628B	1067 mm x 30,5 m (42 in x 100 ft)	848412013580	Worldwide
	Q6630B	1524 mm x 30,5 m (60 in x 100 ft)	848412013597	Worldwide
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see HPLFMedia.com/mediawarranties . To obtain warranty service, please contact Brand Management Group customer support at HPLFMedia.com/hp/en/contactus .			

¹ HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See HPLFMedia.com/hp/ecosolutions for details.



For detailed information on the HP large format print media portfolio and to order, visit HPLFMedia.com

