

Sunset SUV Fine Art Paper 210g



Sunset SUV Fine Art Paper 210g provides the eco-solvent and UV-curable solution for high-volume fine-art and photography reproduction. This soft-textured etching surface texture is ideal for producing art prints for the décor market, particularly for print service providers looking for cost-conscious, high-performing alternatives to aqueous-based fine art papers. Color profiles available for many models.

Product Highlights

Features	Strengths	Applications
Eco-solvent, latex and UV Ink compatible	Soft-textured etching surface for detailed images and accurate colors	Art reproductions (giclée)
Heavy-weight, natural white matte surface	Consistent quality with quick supply turn-around	Fine-art photographs and unframed cards
Acid- and lignin-free for archiving	Fulfills gap in market for a competitively priced, SUV-compatible fine-art, quality paper	Large-volume fine-art production

Product Properties

Properties	Description
Unit	1 Roll
Roll Size	3-inch core
Material	Alpha cellulose. Matte surface
Thickness	11 mil
Basis Weight	280g
pH Value	7.5 - 9.5
Whiteness	96.8
Printer/Ink Compatibility	Compatible with eco-solvent and UV ink
Software Settings	A heavy-weight coated, or enhanced matte paper setting is the appropriate starting point, however, we recommend that you try different settings to achieve optimum performance for your specific application.
Color Matching	For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and/or color matching software.
Finishing/Post Processing	Using a finish varnish or spray will help protect your print from damage, effects of UV light and environmental attack
Optimal Print Environment	68° F - 77° F, 50% R.H
Optimal Service Environment	For end use: 0° F - 300° F, 50% relative humidity
Handling Recommendations	All digital fine art medias are fragile and need to be handled with care. Try not to touch the surface of the paper, always hold the paper by the edges and wear cotton gloves if necessary. After printing, leave prints open to the air to fully dry (24 hours is recommended)
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the LexJet ship date when stored in proper conditions.

Note:

The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire cognitions. Consult an architect or

fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.

Item Details

Size	SKU	UPC
54in x 100ft	LFASUV54100	
60in x 100ft	LFASUV60100	