Durability with Original HP Inks on a L5xx			Measured in years							
Digital Print Media	Graphic Protection Overlaminate	Unprinted	Indoor home or office, unlaminated	Indoor home or office, laminated	Commericial window unlaminated	Commercial window laminated	Outdoor, unlaminated	Outdoor, laminated	Water Resistant without lamination	
HP Prime Gloss CP	HP Gloss or Matte Polymeric Overlaminate	>7	>5	>10	>5	>10	>4	>10	•	
HP Prime Gloss Air GP	HP Gloss or Matte Polymeric Overlaminate	>7	>5	>10	>5	>10	>4	>10	•	
HP Prime Matte Air GP	HP Gloss or Matte Polymeric Overlaminate	>7	>5	>10	>5	>10	>4	>10	•	
HP Prime Matte Air GR	HP Gloss or Matte Polymeric Overlaminate	>7	>5	>10	>5	>10	>4	>10	•	
HP Optimal Gloss Air GRP	HP Gloss or Matte Polymeric Overlaminate	>7	>7	>10	>5	>10	>4	>10	•	
HP Grip Matte Polymeric Air	HP Gloss or Matte Polymeric Overlaminate	tbc	tbc	tbc	tbc	tbc	tbc	tbc	•	

Tested on a HP L5xx with Original HP 831 & 871 Latex Inks

For more information, see www.hplfmedia.com/hp/en/printpermanence. Display permanence rating for interior displays/away from direct sunlight, not under glass by HP Image Permanence Lab. Interior in-window display ratings by HP Image Permanence Lab. HP predictions based on test data under Xenon-Arc illuminant — calculation assumes 6,000 Lux/12 hr day. Outdoor display permanence rating according to SAE J2527; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change.