

LexJet 9.5 Mil Premium Satin Photo Paper



LexJet's 9.5 mil Premium Satin Photo Paper is a low-gloss, resin-coated photo paper with a weight (240 gsm) and thickness (9.5 mil) comparable to other popular inkjet photo papers. LexJet 9.5 mil Premium Satin Photo Paper was designed for all of your Photo Paper needs. The paper is sufficiently water-resistant to avoid damage during everyday use. Plus, this product features a wide color gamut and high white point for greater contrast.

LexJet 9.5 mil Premium Satin Photo Paper can be used on many pigment and dye ink printers from Canon, Epson, and HP, and is engineered for the latest inksets, including Canon Lucia, Epson UltraChrome K3 HDR and HP Vivera.

- Color profiles are available for many models.
- All rolls require a 3-in. spindle or core adapter.

Product Highlights

Features
Satin, low-glare finish
9.5 mil, 240 gram photo paper
New and improved inkjet coating with wider color gamut

Product Properties

Properties	Description
Unit	1 Roll
Roll Size	3in Core
Material	Resin-coated (RC) photo paper
Gauge	9.5 mils
Basis Weight	240g
Whiteness	145 CIE
Opacity	86
Gloss Level @ 60°	17% +/-5
Surface Finish	Satin
Printer/Ink Compatibility	Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks.
Imaging Side	Material is packaged with printable side facing up. Printable surface can be identified by a slight tackiness.
Finishing/Post Processing	Pressure-sensitive vinyl laminates like LexJet's GraphicsGuard with UV inhibitors can be applied to increase the fade and abrasion resistance of the image. Before applying the laminate, allow the image to dry for 24 hours. Residual solvent trapped beneath a laminate as a result of insufficient dry time can cause color shifts.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Optimal Print Environment	70° F (21° C), 50% R.H
Optimal Service Environment	For printing: 60° - 80° F, 50% Relative Humidity.
Handling Recommendations	Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials. Rolls of LexJet film are supplied with the coated side facing out.
Software Settings	The coating on this product is engineered for better than 300% ink coverage. A photo luster, satin or semi-gloss setting is the recommended starting point. However, we recommend a custom ICC profile for optimal results. Please refer to www.lexjet.com for starting-point ICC profiles for some printers.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the LexJet ship date when stored in proper

Note:

The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire cognitions. Consult an architect or fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.

Item Details

Size	SKU	UPC
24in x 100ft	SPSM2400	848412001273
36in x 100ft	SPSM3600	848412001280
44in x 100ft	SPSM4400	848412001297
8.5in x 11in - (300 Sheets)	SPSM8511	848412001235

Product Performance & Suitability

All of the descriptive information and recommendations for the use of LexJet products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by LexJet. All purchasers of LexJet products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (Including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.