

Product Bulletin

GF 229

WallMark® Canvas Embossed Vinyl Film

GF 229 is a 6.0 mil embossed canvas pattern matte white semi rigid calendared vinyl film. GF 229's pressure sensitive adhesive is specially formulated microsphere acrylic removable backed by a 90# layflat liner. The combination of vinyl and adhesive allows removability of this product from normal wall surfaces. The 90# tight release digital liner provides excellent stability for processing using standard solvent and UV curable and latex digital inks common to wide format digital printing systems.

Applications

GF 229 is designed for wall murals, decals and graphics to most types of smooth painted interior walls. This includes most flat, semi-gloss and gloss paint finishes. The surface must be smooth and clean prior to application. If applying to new paint consult the paint manufacturer for proper drying conditions before GF 229 application. Not designed for coated/sealed/treated stainless steel, brass or bronze surfaces.

Burn Rating

ASTM E84 Class 1 or A Rating

Thickness

Film	6.0 mils.
Adhesive	0.8 to 1.0 mil.
Liner	6.7 mils.
(Thickness variation +/- 10%)	

Dimensional Stability Temperature Ranges

Good.	
Minimum application temperature	+40°F.
Service temperature	-40°F to +200 F.

Removability

Removable up to 1 year under normal interior conditions.

Adhesion

To glass	10 oz. / in.
To standard test panels	10 oz. /in.

Tested according to PSTC-101 Method A procedures with 24 hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Bond to wall surfaces may vary. Test thoroughly before production.

Water Resistance Humidity Resistance Storage Stability

Limited immersion resistance. Test for specific application.
Good.
One (1) year shelf life when stored at 70° F and 50% relative humidity.

Product Code

GF 229 Sizes 54" x 100' 60" x 100'

Recommendations

Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in vinyl degradation.



*Manufacturers of
Pressure Sensitive Films*

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537
Web Site: www.generalformulations.com • e-mail: info@generalformulations.com

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions of Sale, Including Disclaimer of Warranties and Limitation of Liability.