

LexJet 6 Mil Textured Indoor Floor & Wall Vinyl



LexJet 6 Mil Textured Indoor Floor & Wall Vinyl is a matte, semi-rigid calendared vinyl with a specially formulated high-tack removable pressure-sensitive adhesive that is backed by a 135gsm lay-flat liner.

This special combination of vinyl and adhesive allows the removability of this product from normal wall surfaces. Designed for wall murals, decals and graphics, LexJet 6 Mil Textured Indoor Floor & Wall Vinyl sticks to most flat, semi-gloss, and gloss painted surfaces. The 135gsm tight-release liner provides excellent stability when printed with latex, solvent and UV curable inks.

The material has an R10B slip-certification for safe use on floor graphics.

Product Highlights

Benefits	Applications	Customers
Designed for easy installation, repositioning and removal without wrinkling or tearing	Wall Murals	Print Service Providers
Slip-resistant for floor graphics	Wall Cut-outs	Graphic Artists
Excellent stability	Decals	Sign Shops
Matte finish for vivid graphics	Indoor and Short-term	Retail
Class A, ASTM E84 flame resistance	Outdoor Signage	
Ability to contour cut and apply without stretching	Point-of-sale Displays	
	Trade Show Graphics	

Product Properties

Properties	Description
Material Type	Adhesive-backed embossed canvas semi-rigid calendared vinyl film
Gauge	150 microns
Weight without Liner	410 gsm
Opacity	98%
Core Size	3-in
Finishing	Matte
Optimal Service Temperature	-40°F to +200°F (-40°C to +93°C)
Ideal Storage Conditions	70°F (21°C) and 50% relative humidity
Color	White
Ink Compatibility	Latex, Solvent, and UV curable inks
Adhesion	To glass 18 N/25 mm (FTM01). To standard test panels 10 N/25 mm (FTM01) Individual values may vary. Bond to wall surfaces may vary. Test thoroughly before production.
Shelf Life	1 year under normal conditions
Flame Resistance	ASTM E84 Class 1 or A Rating
Liner	Layflat liner
Liner Thickness	135 gsm
Adhesive Thickness	25 microns
Temperature Range	Minimum application temperature: +40°F (+4°C).
Dimensional Stability	Good
Removability	Removable up to 1 year under normal interior conditions.
Water Resistance	Limited immersion resistance. Test for specific applications.
Humidity Resistance	Good
Slip Resistance	R10B certification for barefoot and wet areas

Item Details

Size	SKU
54in x 100ft	LJTIFWV54

Product Performance & Suitability

All the descriptive information and recommendations for the use of LexJet products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by LexJet. All purchasers of LexJet products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (Including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.