



Trade name: CLEARSHIELD TYPE C SATIN LL

Version: 1 /

Date revised: 19.06.2015

Substance number: 3602XX703

Replaces Version: - / WORLD

Print date: 21.07.16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

CLEARSHIELD TYPE C SATIN LL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Liquid laminate

1.3. Details of the supplier of the safety data sheet

Address

Marabu North America
2460A Remount Road
29406 North Charleston, SC
Telephone no. 843-886-0094
Information provided Department product safety
by / telephone
E-mail address of PRSI@marabu.de
person responsible
for this SDS

1.4. Emergency telephone number

CHEMTREC 703-527-3887 CCN5004

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

This product is not classified hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

EUH208 Contains A mixture of: 5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and 2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1), 1,2-Benzisothiazol-3(2h)-one, May produce an allergic reaction.

Supplemental information

EUH210 Safety data sheet available on request.

2.3. Other hazards

No special hazards have to be mentioned.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Water containing liquid laminate based on polyurethane

Hazardous ingredients

1,2-Benzisothiazol-3(2h)-one

CAS No. 2634-33-5

EINECS no. 220-120-9

Concentration < 0,05 %



Trade name: CLEARSHIELD TYPE C SATIN LL

Version: 1 /

Date revised: 19.06.2015

Substance number: 3602XX703

Replaces Version: - / WORLD

Print date: 21.07.16

Classification (Regulation (EC) No. 1272/2008)

Aquatic Acute 1	H400
Skin Sens. 1	H317
Acute Tox. 4	H302
Skin Irrit. 2	H315
Eye Dam. 1	H318
Acute Tox. 2	H330
Aquatic Chronic 2	H411

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1	H317	>= 0,05
--------------	------	---------

A mixture of: 5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and 2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1)

CAS No. 55965-84-9

Concentration < 0,0015 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 3	H331
Aquatic Chronic 1	H410
Aquatic Acute 1	H400
Skin Sens. 1	H317
Skin Corr. 1B	H314
Acute Tox. 3	H311
Acute Tox. 3	H301

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Corr. 1B	H314	>= 0,6
Eye Irrit. 2	H319	<= 0,06 < 0,6
Skin Irrit. 2	H315	<= 0,06 < 0,6
Skin Sens. 1	H317	>= 0,0015

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed**Hints for the physician / treatment**



Trade name: CLEARSHIELD TYPE C SATIN LL

Version: 1 /

Date revised: 19.06.2015

Substance number: 3602XX703

Replaces Version: - / WORLD

Print date: 21.07.16

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO₂, powders, water spray/mist, Not be used for safety reasons: water jet

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO); dense black smoke; Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in accordance with national regulation

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Further information on storage conditions

Store between 15 and 30 °C in a dry, well ventilated place. Keep container tightly closed. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)



Trade name: CLEARSHIELD TYPE C SATIN LL

Version: 1 /

Date revised: 19.06.2015

Substance number: 3602XX703

Replaces Version: - / WORLD

Print date: 21.07.16

Liquid laminate

SECTION 8: Exposure controls/personal protection

8.2. Exposure controls

Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Respiratory protection

Not applicable.

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness > 0,5 mm

Breakthrough time < 30 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye protection

Use safety eyewear designed to protect against splash of liquids.

Body protection

Not applicable.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	liquid
Colour	milky white
Odour	solvent-like
Odour threshold	
Remarks	No data available
pH value	
Remarks	not determined
Melting point	
Remarks	not determined
Freezing point	
Remarks	not determined
Initial boiling point and boiling range	
Value	100 °C
Flash point	
Remarks	Not applicable
Evaporation rate (ether = 1) :	
Remarks	not determined



Trade name: CLEARSHIELD TYPE C SATIN LL

Version: 1 /

Date revised: 19.06.2015

Substance number: 3602XX703

Replaces Version: - / WORLD

Print date: 21.07.16

Flammability (solid, gas)

Not applicable

Upper/lower flammability or explosive limits

Remarks not determined

Vapour pressure

Remarks not determined

Vapour density

Remarks not determined

DensityValue appr. 1,05 g/cm³

Source calculated value

Solubility in water

Remarks miscible

Partition coefficient: n-octanol/water

Remarks Not applicable

Ignition temperature

Remarks not determined

Viscosity

Remarks

Remarks not determined

Efflux time

Value 30 s

Method DIN 53211 4 mm

Explosive properties

evaluation no

Oxidising properties

evaluation None known

9.2. Other information**Other information**

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reactions when stored and handled according to prescribed instructions.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

No hazardous reactions when stored and handled according to prescribed instructions.

10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).



Trade name: CLEARSHIELD TYPE C SATIN LL

Version: 1 /

Date revised: 19.06.2015

Substance number: 3602XX703

Replaces Version: - / WORLD

Print date: 21.07.16

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Aspiration hazard

No special hazards have to be mentioned.

Experience in practice

The liquid splashed in the eyes may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Other information

There are no data available on the mixture itself.

The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and not classified.

SECTION 12: Ecological information

12.1. Toxicity

General information

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

12.2. Persistence and degradability

General information

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

General information

There are no data available on the mixture itself.

Partition coefficient: n-octanol/water

Remarks Not applicable

12.4. Mobility in soil

General information

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

General information

There are no data available on the mixture itself.

12.6. Other adverse effects

General information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

EWC waste code 08 03 12* waste ink containing dangerous substances



Trade name: CLEARSHIELD TYPE C SATIN LL

Version: 1 /

Date revised: 19.06.2015

Substance number: 3602XX703

Replaces Version: - / WORLD

Print date: 21.07.16

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.
For further information contact your local waste authority.

Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.
Empty containers must be scrapped or reconditioned.
Not emptied containers are hazardous waste (waste code number 150110).

SECTION 14: Transport information

Land transport ADR/RID

Non-dangerous goods

14.1. UN number

UN -

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

Class -

Label -

14.4. Packing group

Packing group -

Transport category 0

14.5. Environmental hazards

-

Marine transport IMDG/GGVSee

The product does not constitute a hazardous substance in sea transport.

14.1. UN number

UN -

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

Class -

Subsidiary risk -

14.4. Packing group

Packing group -

14.5. Environmental hazards

no

Air transport ICAO/IATA

The product does not constitute a hazardous substance in air transport.

14.1. UN number

UN -

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

Class -

Subsidiary risk -

14.4. Packing group

Packing group -

14.5. Environmental hazards

-

Information for all modes of transport

14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.



Trade name: CLEARSHIELD TYPE C SATIN LL

Version: 1 /

Date revised: 19.06.2015

Substance number: 3602XX703

Replaces Version: - / WORLD

Print date: 21.07.16

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

no

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Other information

The product does not contain substances of very high concern (SVHC).

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

CLP categories listed in Chapter 3

Acute Tox. 2	Acute toxicity, Category 2
Acute Tox. 3	Acute toxicity, Category 3
Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Eye Dam. 1	Serious eye damage, Category 1
Skin Corr. 1B	Skin corrosion, Category 1B
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: ***

This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: CLEARSHIELD TYPE C SATIN LL

Version: 1 /

Date revised: 19.06.2015

Substance number: 3602XX703

Replaces Version: - / WORLD

Print date: 21.07.16