HP Latex 800 W Printer

Win high-value jobs with white ink and productive printing—and sharpen vour sustainability edge





Expand into white, produce the highest value iobs

- Extend your portfolio into high-margin stickers and window graphics with the whitest white.¹
- Print white without complexity—automatic recirculation and printhead cleaning reduce manual purging.
- Deliver vivid colors at high speed, get striking contrast using pure blacks, and expect sharp 4point text.
- Choose from a wide application range covering banners/textiles/poster paper, canvas, wallpaper, and vinyl.

Robust, smart, and productive printing

- Drive high productivity with saturated color at speeds up to 388 ft²/hr outdoor², easy spindleless loading.
- Control print operations virtually anytime, anywhere with HP PrintOS tools, and grow with HP Learn trainings.
- Work fast processing reprints and multi-copy jobs with a smart front panel, and store up to 100 jobs.
- Help reduce running costs with cost-effective 3liter HP ink cartridges, changed while the printer runs.

Sharpen your sustainability edge with HP Latex

- Innovative water-based HP Latex Inks—no HAPs³, no required hazard warning labels, and odorless prints.4
- Local HP Eco-Carton outer carton recycling.⁵
- Choose from a wide range of compatible ecoconscious media.6
- HP Latex prints are recyclable, returnable, or nonhazardous and safe for disposal.

For more information, please visit http://www.hp.com/go/latex800series

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://hplatexknowledgecenter.com/

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

¹ Whitest white based on ISO/DIS 23498 compared to competitive alternatives using solvent and UV technologies under \$50,000 USD as of May, 2020. Test performed on black opaque self-adhesive vinyl ((*:4.16 – a:0,48-b:2,34) with 160% UF printmode using HP 873 3-liter White Latex Ink Cartridge. Visual opacity = 91%. ² Outdoor mode (Banner) 4-pass, 100%. Based on internal HP testing in September 2020 on Avery 3001. Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.

³ HP Latex thick were tested for Hazardous Air Pollutants, as defined in the Clean Air Act, per U.S. Environmental Protection Agency Method 311 (testing conducted in 2013) and none were detected. ⁴ There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

⁵ The ink cartridge outer carton is 100% recyclable through local cardboard/paper programs.

See http://www.hp.com/go/mediasolutionslocator.

⁷ Most HP large format paper-based printing materials can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the free, convenient HP Large Format Media take-back program. Programs may not exist in your area. See http://www.HPLEMedia.com/hp/ecosolutions for details. HP large format printing materials, both unprinted and printed with Original HP Latex Inks, are non-hazardous and safe for disposal. Contact your local waste management authority for local area-specific instructions.

Technical specifications

Print	
Printing modes	1313 ft²/hr - Max Speed (1-pass) 388 ft²/hr - High Speed (4-pass) 269 ft²/hr - Production Fast (6-pass) 215 ft²/hr - Production Quality, Textiles and Backlits (8-pass) 183 ft²/hr - High Saturation (12-pass) 151 ft²/hr - High Saturation Backlits and Textiles (14-pass) 183 ft²/hr - White Spot (60%) 99 ft²/hr - White Overflood (60%) 22 ft²/hr - White Underflood (100%) 22 ft²/hr - J Layers Day & Night (160%) ¹
Print resolution	Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex Inks
Ink cartridges	9 (black, cyan, light cyan, light magenta, magenta, yellow, white, HP Latex Optimizer, HP Overcoat)
Cartridge size	3 L
Printheads	10 (2 cyan/black, 2 magenta/yellow, 2 light cyan/light magenta, 2 white, 1 HP Latex Optimizer, 1 HP Overcoat)
Long-term print-to-print repeatability	t 95% of colors ≤ 1.5 dE2000 ²
Media	
Handling	Roll feed, take-up reel, wiper roller ³ , automatic horizontal cutter (for vinyl, banner and canvas ⁴ , paper based media, and film)
Media types	Banners, self-adhesive vinyls, films, fabrics, papers, wall coverings, canvas, synthetics, mesh, textiles
Roll size	10 to 64-in rolls (23 to 64-in rolls with full support)
Roll weight	121 lb
Roll diameter	9.8 in
Thickness	Up to 19.7 mil
Applications	Banners; Displays; Exhibition and event graphics; Exterior signage; Indoor posters; Interior decoration; Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Window graphics; Stickers
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T)
Dimensions (w x d :	 x h)
Printer	101.7 x 34.1 x 55.2 in
Shipping	108.4 x 43.3 x 65.6 in
Operating area	110 x 82.7 in
Weight	
Printer	661 lb
Shipping	963.4 lb
What's in the box	HP Latex 800 W Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, setup poster, documentation software, power cords, air purgers, 2-in spindle adaptor
Environmental rang	 Jes
Operating temperature	59 to 86°F
Operating humidity	20 to 80% RH (non-condensing)
Acoustics	
Sound pressure	60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)
	60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) 7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep)
Sound power	
Sound power Power	
Sound power Power Consumption	7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep) 1.8-2.8 kW (5 kW peak) (printing), 105 W (ready)
Sound power Power Consumption Requirements	7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep) 1.8-2.8 kW (5 kW peak) (printing), 105 W (ready) Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords;
Sound power Power Consumption Requirements Certification	7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep) 1.8-2.8 kW (5 kW peak) (printing), 105 W (ready) Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords;
Sound power Power Consumption Requirements Certification Safety	7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep) 1.8-2.8 kW (5 kW peak) (printing), 105 W (ready) Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 16 A max per power cord IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN
Sound pressure Sound power Power Consumption Requirements Certification Safety Electromagnetic Environmental	 7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep) 1.8-2.8 kW (5 kW peak) (printing), 105 W (ready) Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 16 A max per power cord IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC) Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive),

Ordering information

Product 3

Floddet		
3XD61A	HP Latex 800 W Printer	
Accessories		
21V10A 7HR16A 7HR18A 7HR19A T7U73A	HP Latex 700/800 User Maintenance Kit HP Latex 700/800 Textile Kit Accessory HP Latex 700/800 Ink Collector Foams Kit HP Latex 700/800 Media Loading Accessory HP Latex 500/700/800 Wiper Roller	
Original HP	printing supplies	
4UU93A 4UU94A 4UV95A 4UV96A 4UV97A 4UV98A 4UU96A 4UU96A 4UU96A 4UU96A 4UV62A	HP 836 White Latex Printhead HP 836 Optimizer Latex Printhead HP 836 Black/Cyan Latex Printhead HP 836 Magenta/Yellow Latex Printhead HP 836 Light Cyan/Light Magenta Latex Printhead HP 836 Overcoat Latex Printhead HP 836 Latex Maintenance Cartridge HP 873 3-liter White Latex Ink Cartridge HP 873 3-liter Black Latex Ink Cartridge	
4UV85A 4UV86A 4UV87A 4UV88A 4UV89A 4UV90A 4UV91A	HP 873 3-liter Cyan Latex Ink Cartridge HP 873 3-liter Magenta Latex Ink Cartridge HP 873 3-liter Yellow Latex Ink Cartridge HP 873 3-liter Light Cyan Latex Ink Cartridge HP 873 3-liter Light Magenta Latex Ink Cartridge HP 873 3-liter Optimizer Latex Ink Cartridge HP 873 3-liter Optimizer Latex Ink Cartridge	

Original HP large format printing materials

HP PVC-free Wallpaper (UL GREENGUARD GOLD Certified⁶, FSC[®] certified⁷, meets AgBB criteria⁹) HP Photo-realistic Poster Paper HP Premium Satin Carwas HP Prime Matte Air GP (REACH compliant⁹)

HP Premium Removable Gloss Adhesive Vinyl (REACH compliant⁹)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U13DDE HP 2 year Next Business Day with Defective Media Retention U13DJE HP 3 year Next Business Day with Defective Media Retention U13DNPE HP 1 year Post Warranty Next Business Day with Defective Media Retention U13DTPE HP 2 year Post Warranty Next Business Day with Defective Media Retention

ECO highlights

Inks do not use reactive monomer chemistry, are ozone-free, and meet the ZDHC standard¹ Can win new business with odorless prints, UL ECOLOGO®/UL GREENGUARD Gold Certified ink, and more² High-volume 3-liter HP Eco-Carton ink cartridges—carton-based design significantly reduces plastic

Please recycle printing hardware and eligible printing supplies and prints. Find out how at our website: http://www.hp.com/ecosolutions

¹ See http://www.roadmaptozero.com. Printing with HP Latex Inks avoids the problematic reactive monomers associated with UV printing. Acrylate monomers present in uncured UV inks and UV-gel inks can damage skin. ² There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print. For certifications, see http://www.ul.com/EL and http://www.ul.com/gg.

¹ Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects.
² The color variation between printed jobs has been measured at 12 pass mode on vinyl media following best practices for tiling layouts and within this limit: 95th percentile of pairwise color differences (95%) of colors) ≤ 1 dE2000. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard D5 014-6/E:2012. 5% of colors may experience variations above 1 dE2000. Backlit substrates measured in transmission mode may yield different results. ³ Wiper roller is an optional accessory.

⁴ Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test. ⁵ Textile Kit Accessory required for long runs of textile and porous textile.

⁶ Lextene NL ACCESSOR y required to long funs on texture and portogs texture.
6 UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.ulc.com/gg or http://www.greenguard.org.
7 Trademark license code FSC-C115319.

¹ Trademark license code FSC-C115319.
8 With HP Latex Inks, prints meet AgBB criteria for health-related evaluation of VOC emissions. See http://umweltbundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-evaluation-of-building.
9 This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.



