

LexJet 6 Mil Simple Rigid Matte Vinyl w/HTR



LexJet 6 Mil Simple Rigid Matte Vinyl w/HTR makes it simple to print, install and remove wall graphics, murals and decals. The high tack removable adhesive allows graphics to be repositioned frequently during installation and removes cleanly. LexJet 6 Mil Simple Rigid Matte Vinyl w/HTR is a premium matte, semi-rigid white vinyl film that provides exceptional image quality, ease of handling, perfect for contour cutting and won't curl over time. It is compatible with solvent, low-solvent, UV-curable and latex printers, and is removable for up to one year.

- Easy to print, install and remove
- 6 mil thickness for ease of installation
- Perfect for temporary signage, bumper stickers, POP applications
- Lay flat liner offers good dimensional stability
- For use with latex, low solvent, solvent, and UV-curable inks
- Removable for up to one year

Features	Strengths	Applications
Perfect for temporary signage, point of purchase, bumper sticker and any low surface energy plastics		
Ideal for contour cutting, easy to handle and won't curl over time		
The graphic can be repositioned multiple times during installation		

Property	Description
Unit	1 Roll
Core Size	3in Core
Material	Semi-rigid PVC film
Finish	Matte
Gauge	6 mil
Adhesive	.8 to 1.0 mil high tack removable adhesive
Release Liner	90# stay flat liner
Printer/Ink Compatibility	Compatible with all inkjet printers using low-solvent, solvent, latex and UV-curable ink.
Color Matching	For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and color matching software. However, if these tools are not available use one of the on-board media settings for cast vinyl.

Note:

The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire conditions. Consult an architect or fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.



Property	Description
Finishing/Post Processing	Pressure-sensitive vinyl laminates like LexJet Elite UV Vinyl can be applied to increase the fade and abrasion resistance of the image. Before contour cutting or applying laminate, allow the image to dry for 24 hours. Residual solvent trapped beneath a laminate as a result of insufficient dry time can cause color shifts.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Removability	Designed for temporary application of decals and graphics to most types of surfaces. The surface must be smooth and clean prior to application.
Expected Life	Removable up to one year under normal interior conditions.
Optimal Print Environment	70° F (21° C), 50% R.H
Service Temp. Range	-40° - 200° F
Minimum Application Temp.	+30° F
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store vertically in original packaging.
Shelf Life	1 yr shelif life when stored in proper conditions.

Size	SKU	UPC
54in x 150ft	SRMVHTR54150	

Note:

The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire conditions. Consult an architect or fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.