



Substrate		DIN 60001	min. 80 % recycled polyester (widths ≤ 310 cm / 122 inch) 100 % polyester (width 510 cm / 201 inch)
Weave		DIN ISO 9354	woven fabric
Weight approx.		DIN EN ISO 2286-2	240 g/m ²
Fire retardancy		DIN 4102 B1, B-s3,d0, NFPA 701, Class A - ASTM E84-20	yes
Application			indoor
Width		DIN EN ISO 2286-1	max. 510 cm / 201 inch (see overview)
Print side			width < 3 m: print side outside width > 3 m: print side inside
Roll length			30 - 65 ± 0,5 m
Care instruction		DIN EN 12956	scrub resistant (grade 5) according to instruction*
Type of ink			all kinds of solvent inks, UV-curable inks**, latex inks

Advantages

- matt surface
- available in large width
- no curling
- dirt repellent
- opaque
- trimming cold (no fraying)

Applications

- roll up
- banner
- frontlit
- frame tensioning systems
- art reproduction
- wall covering***

For information and to order, visit jm.globalbmg.com

Classified as Type II - Category V in accordance to ASTM F793/793M-15

* please have a look at the cleaning instructions on www.jm-mediatex.com

** please consider the risk of curling because UV-curable inks will still be hardening after a while

*** please test in advance; the adhesive behavior depends on the surface applied



All details are nominal values and are subject to change within usual tolerances (± 5 %). The information provided in this document is based on current knowledge and experience. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor. date: 04/2021