



HEAT TRANSFER TECHNOLOGIES

SUBLI RANGE

SUBLI 1510+ / SUBLI 1812+ SUBLIMAXI 2513



Touch Screen



Set programs



Pneumatic



Suitable for :


- Sports goods
- Advertising, flags, banners, accessories
- Large photos, posters
- Transfer on hard substrates (ceramic, aluminium, plastic, wood...)
- Textile : home finishing, apparel, curtains...
- Awning

- Ideal for sublimation with good productivity and flexibility
- Fast startup ! (15 to 20min)
- Plate in rectified high quality aluminium
- Perfect heat distribution (multiple heating zones)
- PT100 platinum heat sensor
- 2-year guarantee on the machine
- 10-year guarantee on heating elements
- Front load motorized double sliding plate
- Manufactured in France.

OPTIONAL ACCESSORIES




Sublimation paper



Polyester Felt



Nomex® Cover



Teflon Cover



Air extractor



Compressor



Email



Phone



Address

SefaNorthAmerica@ServRight.com Office: 801-390-1761

Sefa North America
2090 N Redwood Rd. #70
Salt Lake City, UT 84116



Chemica | Stilscreen | Sefa | Elms | Sporting ID

TECHNICAL CHARACTERISTICS

Type	Pneumatic
Operation	SLIDE - Tray with double automatic drawer
Platen size	SUBLI-1510+ : 62"x42" SUBLI-1812+ : 71"x47" SUBLIMAXI-2513 : 100"x51"
Weight	SUBLI-1510+ : 2,204.5 lbs. SUBLI-1812+ : 3,074 lbs. SUBLIMAXI-2513 : 4,807 lbs
Max thickness	Max Thickness 1.75 inches
°C / °F Max	°C/°F Max 220 °C / 429 °F
Power	SUBLI-1510+ : 20,25 KW / 32 A SUBLI-1812+ : 30,25 KW / 46 A SUBLIMAXI-2513 : 35 KW / 56 A
Power supply	400 V 3-phases
Applications	ChromaLuxe, sublimation rigid substrates, textile sublimation

SETTINGS



Touch electronics developed by Sefa
Precise and fast regulation (PID control)

Several Languages to choose from
including English

4 recordable programs
Counter with reset
Double timer
Energy saving

From 0 to 600 s (precision +/- 1%). From
0 to 220°C (precision +/- 1%).

Heating time to reach 180°C : 15 min.


OPTIONAL ACCESSORIES




ASP-SUBLI
Exhaust system to evacuate
sublimation fumes.



COMP-XXX
Silent compressor
COMP-111 : 50L. 111Lt/min.
for SUBLI-1510+
COMP-240 : 50L. 240Lt/min.
for SUBLI-1812+
COMP-300 : 150L. 300Lt/min.
for SUBLIMAXI-2513



FEU-XXX
Polyester felt for lower plate.
FEU-022 (SUBLI-1510+)
FEU-019 (SUBLI-1812+)
FEU-025 (SUBLIMAXI-2513)



TOI-T1510+ / T1812+ / T2513
Teflon cover for heating
plate.



TOI-N1510+ / N1812+ / N2513
Nomex® cover for heating
plate.



PAP-TP-SE64300 / SE44100
High quality sublimation
paper available in 44"x30m
and 64"x100m.

DIMENSIONS

SUBLI-1510+



SUBLI-1812+



SUBLIMAXI-2513

