

TECHNICAL DATA SHEET

GF 260 WINDOWMARK™

6.0 MIL MATTE WHITE PERFORATED VINYL (60/40)
CLEAR REMOVABLE ADHESIVE

GF 260 is a 6.0 mil perforated high performance vinyl film with a white print side and a black see through side coated with a clear low tack repositionable removable solvent acrylic pressure sensitive adhesive designed for exterior/outside mounted one way view-through window graphics. The vinyl will accept a variety of wide format digital printing inks including solvent, eco-solvent, UV and Latex. The dual layflat liner construction, perforated/solid liner, offers good dimensional stability in a variety of ambient conditions and is cross compatible with wide-format digital inkjet printer platforms including UV. The adhesive is designed to cleanly remove from glass with little to no adhesive residue.

| PRODUCT NAME | 260 |
|---|---|
| FILM | |
| Film Type | White/Black Perforated Vinyl |
| Film Thickness (mils/μm) | 6.0 / 152 (+/- 10%) |
| Film Weight (gsm) | 120 |
| Gloss (60°) | N/A |
| Opacity (%) | N/A |
| Tensile Strength (lbs/in) | N/A |
| Elongation (%) | N/A |
| Dimensional Stability (FTM 14) | MD ≤ 0.30 mm / CD ≤ 0.30 mm |
| ADHESIVE | |
| Adhesive Type | Solvent Acrylic |
| Adhesive Thickness (mils/μm) | 0.8-1.0 / 20-25 |
| Adhesive Color | Clear |
| Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min | 1.0 / 4.4 |
| Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs | 1.7 / 7.4 |
| Peel Strength on Glass (lbs/in) / (N/25mm) 15 min | 2.0 / 8.8 |
| Peel Strength on Glass (lbs/in) / (N/25mm) 24 hrs | 2.0 / 8.8 |
| LINER | |
| Liner Weight (#/gsm) | 104 / 170 |
| Liner Type | Dual Layer (Perforated/Solid) White 2-Sided PE-Coated Kraft |
| Liner Thickness (mils/μm) | 9.2 / 235 |
| Release Force @ 300" / min (g/2") | 50-150 |
| PERFORMANCE GUIDANCE | |
| Application Temperature | ≥ +40 °F |
| Service Temperature | 0 °F to 150 °F |
| Shelf Life | 1 year |
| Storage Temp / Rel. Humidity | 70 °F / 50% |
| Outdoor Durability | Up to 2 years |
| Removability | Up to 1 year |

TECHNICAL DATA SHEET

GF 260 - 6.0 MIL MATTE WHITE PERFORATED VINYL (60/40) CLEAR REMOVABLE ADHESIVE

| PRODUCT SNAPSHOT | APPLICATIONS | INK TYPE |
|---|--|---|
| APPLICATION <input type="radio"/> WET APPLY <input checked="" type="radio"/> DRY APPLY <input type="radio"/> LAMINATING <input type="radio"/> MOUNTING <input checked="" type="radio"/> DIE CUTTABLE <input type="radio"/> HOT STAMP <input type="radio"/> THERMAL DIE <input checked="" type="radio"/> FLATBED CUTTABLE | <input checked="" type="radio"/> POP/RETAIL <input type="radio"/> WALL <input type="radio"/> WRAP <input checked="" type="radio"/> WINDOW <input type="radio"/> FLOOR <input type="radio"/> TRANSLUCENT <input type="radio"/> FLEET <input checked="" type="radio"/> GENERAL SIGNAGE <input checked="" type="radio"/> INDOOR <input checked="" type="radio"/> OUTDOOR | <input checked="" type="radio"/> SOLVENT <input checked="" type="radio"/> ECO-SOLVENT <input checked="" type="radio"/> LATEX <input checked="" type="radio"/> UV CURABLE <input checked="" type="radio"/> SCREEN <input checked="" type="radio"/> OFFSET (UV CURABLE) <input type="radio"/> OFFSET (CONVENTIONAL) |
| SUBSTRATES/SURFACES <input type="radio"/> OEM PAINTED METAL <input type="radio"/> PAINTED ALUMINUM <input type="radio"/> STAINLESS STEEL <input checked="" type="radio"/> GLASS <input checked="" type="radio"/> ACRYLIC | | |

FAQS

| | |
|---|---|
| What applications are GF 260 good for? | GF 260 works great with flat, smooth transparent surfaces. An ideal solution for temporary store front applications and medium-term applications requiring view-through capabilities and bond to windows. |
| What if I leave GF 260 on past it's optimal removability time frame? | GF 260 will always be removable, but you may have some percentage of adhesive transfer when left on past the 1 year clean removal timeline. |
| Is GF 260 good for vehicle windows? | When this product is used on vehicles some states have minimum light transmission regulations. The user of this product is responsible for complying with these regulations. |
| If I want to laminate my graphic print, do I need to use an optically clear laminate? | Yes. In most cases where a laminate is used, an optically clear laminate is recommended for optimal view-through capabilities. Using standard laminates can result in less clarity. We recommend our GF 842 Opti-Mark™ Optically Clear Cast laminate. |