DreamScape® Holographic Specification Sheet v:050719

Product Name: DreamScape Déjà vu, Limelight and Rave – 20 oz. (457g/m²) Type II

Description: Commercial grade printable vinyl wallcovering media with a holographic surface.

Construction: Polyester/vinyl face with non-woven backing

Packaging: 3" core, wound print side out, wrapped in black poly-bag, shipped in heavy-duty cardboard tube

Installation: Standard commercial wallcovering pastes, primers and techniques.

For indoor use in environmentally controlled spaces.

<u>SPECIAL INSTALLATION INSTRUCTION</u> This wallcovering contains metallic particles and can conduct electricity. To avoid possible fire hazards or electric shock, wallcovering should not come in contact with or extend into electrical-outlet boxes or light-switch boxes. Turn

off all electricity to the room prior to starting installation.

<u>SPECIAL NOTE</u> Please be aware this wallcovering may interfere with broadcast signals, such as Wi-Fi and radio reception, because of the polyester/metal layer. Tests have shown 5% or less impact on signals when the receptor is totally encased in wallcovering but the

interference may vary depending on the specific installation conditions.

Ink Compatibility: UV curable, Solvent and Latex ink systems

CAUTION: This product is highly reflective. Check with your printer manufacturer for their recommendations on

printing reflective material.

Availability:

US Metric 54" 1.37m,

 Lengths:
 25yds, 50yds
 30m, 50m

 Trial Rolls:
 27"x15'
 .686m x 4.57m

Weight & Thickness:

Mold/Mildew:

US Metric

 Product Weight:
 20oz. per lineal yard (13 oz. per sq yd)
 457g/m²

 Thickness
 0.016 in to 0.017in
 0.414mm to 0.432mm

Type II Properties: Passes all criterion for WA 101 Type II properties including:

Break StrengthTear StrengthCold CrackHeat AgingShrinkageStain ResistanceCoating Adhesion (Bond)ColorfastnessWashabilityScrubabilityBlockingCrocking

Specifications: Federal Specification:

CCC-408-D Type II*
WA Specification:

WA-101, NSF/ANSI 342 Sustainability Standard

NFPA Life Safety Code 101*

Fire Test Ratings: ASTM-E84 Tunnel Test Passed Class A

EU Class Flame (EN15102)

BS476 Parts 6&7

CAN/ULC-S102

ASTM-G21 Specifications

Passed Class B, s2

Passed all requirements

Passed all requirements

Sustainability: NSF-342 - Certified for Silver compliance for all 20 oz wallcovering constructions

HPD – Health Product Declaration available

 ${\sf EPD-Environmental\ Product\ Declaration\ available-UL\ third\ party\ certified\ for\ wall covering\ industry\ average}$

Low VOC – Meets California CDPH Standard for Schools and Offices when tested to CA 01350

Contributes to LEED v4

Meets or exceeds EU Toxicity standard EN 12149 A,B,C for heavy metals and formaldehyde

Phthalate free formulation Prop 65 compliant

Manufactured without the use of Brominated flame retardants

For non-woven backed constructions –

11% post-consumer content in total product – using recycled polyester, cellulose

100% of backing fiber content is post-consumer fiber

Warranty: 5 Year Warranty against manufacturing defects. Additional information regarding warranty is available on our website at

http://www.dreamscapewalls.com/

Comments: *Meets or exceeds requirements for flame spread, smoke developed and flashover.

DreamScape – a division of Roysons Corp. ● 40 Vanderhoof Ave. ● Rockaway, NJ 07866