

KODAK

Premium Rapid-Dry Photographic Lustre Paper / 255g

Produce excellent image quality with a fast dry-time

Instant dry-time

KODAK Premium Rapid-Dry Photographic Lustre Paper / 255g is a genuine resin-coated paper that provides excellent image quality and instant dry times with dye and pigment inks.

High -uality photo reproductions

Premium Rapid-Dry Lustre photographic paper offers the ideal weight, thickness and finish for high quality photographic reproductions. With superb color image quality, guaranteed performance for longevity, universal compatibility with piezo and pigment systems, and the power of the Kodak brand behind it, this media is ready-made for the professional photographer.

FSC®-certified

Meet environmental objectives with this FSC®-certified paper.

FEATURES:

- · Microporous, instant-dry coating
- Superior image quality, wide color gamut, enhanced density and sharpness
- Thermal and cold laminate compatible
- FSC®-certified paper

APPLICATIONS:

- · High-end posters and signage
- Photo enlargements
- Point of purchase graphics and displays

| US Size | Euro Size | Quantity | SKU |
|------------|--------------------|----------|----------|
| 17" x 100' | 43,1 cm x 30,5 m | 1 Roll | KPRDPL17 |
| 24" x 100' | 60,9 cm x 30,5 m | 1 Roll | KPRDPL24 |
| 36" x 100' | 91,4 cm x 30,5 m | 1 Roll | KPRDPL36 |
| 42" x 100' | 103,6 cm x 30, 5 m | 1 Roll | KPRDPL42 |
| 44" x 100' | 111,7 cm x 30,5 m | 1 Roll | KPRDPL44 |
| 60" x 100' | 152,4 cm x 30,5 m | 1 Roll | KPRDPL60 |



KODAK

Premium Rapid-Dry Photographic Lustre Paper / 255g

| Properties | Specifications | | |
|---------------------------|---|--|--|
| Material | Resin-coated photo paper | | |
| Gauge | 10 mil, 255g | | |
| CIE Whiteness | >130 | | |
| Environmental | FSC®-certified paper | | |
| Opacity | >90 | | |
| Printer/Ink Compatibility | Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks. | | |
| Software Setting | The photo lustre paper setting in most RIPs is appropriate; however, we recommend a custom ICC profile for optimal results. Please refer to www.brandmangagementgroup.com for ICC profiles for some printers. | | |
| Light Fastness | The photo lustre paper setting in most RIPs is appropriate; however, we recommend a custom ICC profile for optimal results. Please refer to www.brandmangagementgroup.com for ICC profiles for some printers. | | |
| Finishing/Post Processing | It is always recommended that a protective laminate be applied after printing. Hand applying laminate is not recommended. Pressure-sensitive or thermal laminates can be used. Before applying the laminate, allow the image to dry for 24 hours. | | |
| Handling Recommendations | Avoid touching the coated surface and use cotton gloves when handling inkjet coated materials. Rolls of Kodak inkjet media come with the coated side facing out. | | |
| Ideal Storage Conditions | 70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.) | | |
| Shelf Life | 1 year from the BMG ship date when stored in proper conditions. | | |





AMS: 888-893-4668 EMEA: +34 935 479 700 APJ: +61 2 8038 5013

KODAKWFMedia.com

The KODAK trademark, logo, and trade dress are used under license from KODAK.

© 2022, Brand Management Group

