

KODAK

Premium Rapid-Dry Photographic Glossy Paper / 255g

Produce excellent image quality with a fast dry-time

Instant dry-time

KODAK Premium Rapid-Dry Photographic Glossy Paper / 255g is a genuine resin-coated paper that provides excellent image quality and instant dry times with dye and pigment inks.

High -uality photo reproductions

Premium Rapid-Dry Glossy photographic paper offers the ideal weight, thickness and finish for high quality photographic reproductions. With superb color image quality, guaranteed performance for longevity, universal compatibility with piezo and pigment systems, and the power of the Kodak brand behind it, this media is ready-made for the professional photographer.

FSC®-certified

Meet environmental objectives with this FSC®-certified paper.

FEATURES:

- · Microporous, instant-dry coating
- Superior image quality, wide color gamut, enhanced density and sharpness
- Thermal and cold laminate compatible
- FSC®-certified paper

APPLICATIONS:

- · High-end posters and signage
- Photo enlargements
- Point of purchase graphics and displays

US Size	Euro Size	Quantity	SKU
17" x 100'	43,1 cm x 30,5 m	1 Roll	KPRDPL17
24" x 100'	60,9 cm x 30,5 m	1 Roll	KPRDPG24
36" x 100'	91,4 cm x 30,5 m	1 Roll	KPRDPG36
42" × 100'	103,6 cm x 30, 5 m	1 Roll	KPRDPG42
44" × 100'	111,7 cm x 30,5 m	1 Roll	KPRDPG44
60" x 100'	152,4 cm x 30,5 m	1 Roll	KPRDPG60



KODAK

Premium Rapid-Dry Photographic Glossy Paper / 255g

Properties	Specifications		
Material	Resin-coated photo paper		
Gauge	10 mil, 255g		
CIE Whiteness	>130		
Environmental	FSC®-certified paper		
Opacity	>90		
Printer/Ink Compatibility	Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks.		
Software Setting	The photo lustre paper setting in most RIPs is appropriate; however, we recommend a custom ICC profile for optimal results. Please refer to www.brandmangagementgroup.com for ICC profiles for some printers.		
Light Fastness	The photo lustre paper setting in most RIPs is appropriate; however, we recommend a custom ICC profile for optimal results. Please refer to www.brandmangagementgroup.com for ICC profiles for some printers.		
Finishing/Post Processing	It is always recommended that a protective laminate be applied after printing. Hand applying laminate is not recommended. Pressure-sensitive or thermal laminates can be used. Before applying the laminate, allow the image to dry for 24 hours.		
Handling Recommendations	Avoid touching the coated surface and use cotton gloves when handling inkjet coated materials. Rolls of Kodak inkjet media come with the coated side facing out.		
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.)		
Shelf Life	1 year from the BMG ship date when stored in proper conditions.		





AMS: 888-893-4668 EMEA: +34 935 479 700 APJ: +61 2 8038 5013

KODAKWFMedia.com

The KODAK trademark, logo, and trade dress are used under license from KODAK.

© 2022, Brand Management Group

