

ELEMENTS

QUARRY

Bianco Bright White Satin Canvas SUV

Quarry Bianco Bright White Satin Canvas SUV is a radiant white polycotton satin canvas that delivers a durable and sturdy option for high-volume commercial décor. It is compatible with various printing methods, including latex, solvent, and UV curable printers.

The canvas has a thickness of 18 mil and a weight of 400 gsm, providing a substantial and robust surface for printing. The satin finish adds a subtle texture to the printed image, enhancing its visual appeal. The canvas is designed to work with SUV inks, allowing for a wide color gamut and vibrant, long-lasting prints.

The media opacity of Quarry Bianco is opaque, ensuring that the printed image is not affected by any underlying surface. The canvas is made of a 65/35 blend of polyester and cotton, providing an ideal balance of strength and flexibility. With a 2-over-1 weave, the canvas has a smooth surface perfect for reproducing fine details and sharp images.

The gloss level of the canvas is measured at 60°, with a reading of 5, giving the printed image a moderate sheen. The brightness level of the canvas is 94, while the whiteness level is 111, ensuring that the printed image is crisp and vibrant. The canvas has a PH value of 5, ensuring that the printed image is resistant to fading. With its technical specifications, the Quarry Bianco Bright White Satin Canvas SUV provides accurate and consistent color reproduction, making it an excellent option for professional printing.

PRINTER/INK COMPATIBILITY

Compatible with Original HP Latex Inks; solvent, low-solvent, and UV-curable inks.

COLOR MATCHING

For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and/or color matching software.

FINISHING/POST PROCESSING

No post processing or finishing is required on this canvas, however, a clear fixative may be applied to enhance certain areas of the print.

OPTIMAL PRINT ENVIRONMENT

66-77° F, 20-60% Relative Humidity.
For end use: 0-300° F

HANDLING RECOMMENDATIONS

Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials.



PRODUCT SPECIFICATIONS

Thickness	18 mils
BASIC Weight	400 gsm
Finish	Satin
Ink Type	SUV
Media Opacity	Opaque
Media Type	Canvas
Material	Poly/Cotton
65/35	
Fabric Weave	2 over 1
Gloss Level	60° = 5
Brightness	94
Whiteness	111
Opacity	>99%
PH Value	5
L*a*b* Color Space	L* = 95.80 a* = 1.83 b* = -4.34

MEDIA APPLICATIONS

- Soft Signage
- Wall Murals
- Interior Décor
- Photographers
- POP/ Indoor Signage
- Fine Art
- Gallery Wraps

IDEAL STORAGE CONDITIONS

70° F (21° C), 50% R.H.; Store in original packaging; A controlled environment is recommended.

SHELF LIFE

Greater than 1 year from the LexJet ship date when stored in proper conditions.

SKU	PRODUCT SIZE
QMB3075	30" x 75'
QMB3675	36" x 75'
QMB4475	44" x 75'
QMB5475	54" x 75'
QMB54150	54" x 150'
QMB6075	60" x 75'
QMB60150	60" x 150'
QMB6475	64" x 75'
QMB64150	64" x 150'