

ELEMENTS

QUARRY

Carrara OBA-Free Semi Matte Canvas SUV

Quarry Carrara OBA-Free Semi-Matte Canvas SUV is a polycotton canvas that offers a semi-matte finish with a 2-over-1 weave. It is specifically designed for high-volume commercial décor and compatible with various printing methods, including latex, solvent, and UV curable printers. One of the key features of this canvas is that it is free of OBAs, making it an excellent option for those who want to avoid any potential yellowing or fading over time.



In terms of technical specifications, Quarry Carrara has a thickness of 18 mil and a weight of 385 gsm. The finish is semi-matte, and the media opacity is opaque, making it perfect for high-quality, vibrant prints. The fabric is a poly/cotton blend of 65/35 and provides a durable surface for printing.

The gloss level at 60° is 3, and the brightness is 90, making for a vibrant and eye-catching canvas. The whiteness is 191, and the opacity is greater than 99%, ensuring that your prints are crisp and clear. The PH value is 7, and the LAB color space is $L^* = 95.65$, $a^* = 0.55$, $b^* = -0.25$, indicating a high level of color accuracy and consistency, making it perfect for professional photographers and artists. Quarry Carrara

OBA-Free Semi-Matte Canvas SUV is a rock-solid choice for high-volume commercial décor and offers superior performance.

PRINTER/INK COMPATIBILITY

Compatible with Original HP Latex Inks; solvent, low-solvent, and UV-curable inks.

COLOR MATCHING

For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and/or color matching software.

FINISHING/POST PROCESSING

No post processing or finishing is required on this canvas, however, a clear fixative may be applied to enhance certain areas of the print.

OPTIMAL PRINT ENVIRONMENT

66-77° F, 20-60% Relative Humidity.
For end use: 0-300° F

HANDLING RECOMMENDATIONS

Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials.

PRODUCT SPECIFICATIONS

THICKNESS	18 mils
BASIC WEIGHT	385 gsm
FINISH	Semi-Matte
INK TYPE	SUV
MEDIA OPACITY	Opaque
MEDIA TYPE	Canvas
MATERIAL	Poly/Cotton
	65/35
FABRIC WEAVE	2 over 1
GLOSS LEVEL	60° = 3
BRIGHTNESS	90
WHITENESS	91
OPACITY	>99%
PH Value	7
L*a*b* Color Space	$L^* = 95.65$ $a^* = 0.55$ $b^* = -0.25$

MEDIA APPLICATIONS

- Soft Signage
- Wall Murals
- Interior Décor
- Photographers
- POP/ Indoor Signage
- Fine Art
- Gallery Wraps

IDEAL STORAGE CONDITIONS

70° F (21° C), 50% R.H.; Store in original packaging; A controlled environment is recommended.

SHELF LIFE

Greater than 1 year from the LexJet ship date when stored in proper conditions.

SKU	PRODUCT SIZE
QMC3075	30" x 75'
QMC3675	36" x 75'
QMC4475	44" x 75'
QMC5475	54" x 75'
QMC54150	54" x 150'
QMC6075	60" x 75'
QMC60150	60" x 150'
QMC6375	63" x 75'
QMC6475	64" x 75'
QMC64150	64" x 150'