

Polished Bianco Bright White Gloss Canvas SUV

Quarry Polished Bianco Bright White Gloss Canvas SUV is a radiant white polycotton gloss canvas that boasts a 2-over-1 weave, making it a durable and sturdy option for high-volume commercial décor. It is compatible with various printing methods, including latex, solvent, and UV-curable printers. With a thickness of 18 mils and a weight of 400 gsm, this canvas is robust and provides a substantial surface for printing. The canvas is designed to work with SUV inks, allowing for a wide color gamut and vibrant, long-lasting prints.

The finish of Quarry Polished Bianco is glossy, enhancing its visual appeal. The canvas is made of a 65/35 blend of polyester and cotton, providing an ideal balance of strength and flexibility. With a 2-over-1 weave, the canvas has a smooth surface perfect for reproducing fine details and sharp images.

The gloss level of the canvas is measured at 60°, with a reading of 7.7, giving the printed image a high sheen. The brightness level of the canvas is 92, while the whiteness level is 104, ensuring that the printed image is crisp and vibrant. The media opacity of Quarry Polished Bianco is opaque, ensuring that the printed image is not affected by any underlying surface. The canvas has a PH value of 5, ensuring that the printed image is resistant to fading. Quarry Polished Bianco is a radiant white gloss canvas perfect for high-volume commercial décor.



PRINTER/INK COMPATIBILITY

Compatible with Original HP Latex Inks; solvent, low-solvent, and UV-curable inks

COLOR MATCHING

For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and/or color matching software.

FINISHING/POST PROCESSING

No post processing or finishing is required on this canvas, however, a clear fixative may be applied to enhance certain areas of the print.

OPTIMAL PRINT ENVIRONMENT

66-77° F, 20-60% Relative Humidity.
For end use: 0-300° F

HANDLING RECOMMENDATIONS

Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials.

PRODUCT SPECIFICATIONS

THICKNESS	18 mils
BASIC WEIGHT	400 gsm
FINISH	Satin
INK TYPE	SUV
MEDIA OPACITY	Opaque
MEDIA TYPE	Canvas
MATERIAL	Poly/Cotton
65/35	
FABRIC WEAVE	2 over 1
GLOSS LEVEL	60° = 7.7
BRIGHTNESS	92
WHITENESS	104
OPACITY	>99%
PH Value	5
L*a*b* Color Space	L* = 95.17 a* = 1.29 b* = -2.8

MEDIA APPLICATIONS

- Soft Signage
- Wall Murals
- Interior Décor
- Photographers
- POP/ Indoor Signage
- Fine Art
- Gallery Wraps

IDEAL STORAGE CONDITIONS

70° F (21° C), 50% R.H.; Store in original packaging; A controlled environment is recommended.

SHELF LIFE

Greater than 1 year from the LexJet ship date when stored in proper conditions.

SKU	PRODUCT SIZE
QMPB23075	30" x 75'
QMPB24475	44" x 75'
QMPB25475	54" x 75'
QMPB254150	54" x 150'
QMPB26075	60" x 75'
QMPB26475	64" x 75'