

Kashmir Bright White Production Canvas SUV

Quarry Kashmir Bright White Production Canvas SUV is a premium quality, bright white polyester satin canvas designed for high-volume production runs. It is engineered to work with SUV inks, which are known for producing a wide color gamut and vibrant, long-lasting prints. The canvas is compatible with various printing methods, including latex, solvent, and UV curable printers, making it a versatile option for different printing applications.

The canvas has a thickness of 13.5 mil and a weight of 280 gsm, which makes it lightweight and easy to handle, but still substantial enough for high-volume production runs. The satin finish of the canvas provides a subtle texture that enhances the visual appeal of the printed image. The canvas is made of polyester (PET), known for its durability, resistance to fading, and resistance to water and other environmental factors, making it an ideal choice for long-lasting printed products. The 2-over-1 weave of the canvas provides a smooth surface that is perfect for reproducing fine details and sharp images.

The gloss level of the canvas is measured at 60°, with a reading of 4, providing a moderate sheen that adds a subtle level of depth to the printed image. The brightness level of the canvas is 91, while the whiteness level is 111, ensuring that the printed image is crisp and vibrant. The media opacity of Quarry Kashmir is opaque, ensuring that the printed image is fully saturated and vibrant. The canvas has a pH value of 5, which makes it



PRINTER/INK COMPATIBILITY

Compatible with Original HP Latex Inks; solvent, low-solvent, and UV-curable inks.

COLOR MATCHING

For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and/or color matching software.

FINISHING/POST PROCESSING

No post processing or finishing is required on this canvas, however, a clear fixative may be applied to enhance certain areas of the print.

OPTIMAL PRINT ENVIRONMENT

66-77° F, 20-60% Relative Humidity.
For end use: 0-300° F

HANDLING RECOMMENDATIONS

Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials.

PRODUCT SPECIFICATIONS

Thickness	13.5 mils
BASIC Weight	280 gsm
Finish	Satin
Ink Type	SUV
Media Opacity	Opaque
Media Type	Canvas
Material	PET
Fabric Weave	2 over 1
Gloss Level	60° = 4
Brightness	91
Whiteness	111
Opacity	>93%
PH Value	5
L*a*b* Color Space	L* = 95.11 a* = 0.69 b* = -2.32

MEDIA APPLICATIONS

- Soft Signage
- Wall Murals
- Interior Décor
- Photographers
- POP/ Indoor Signage
- Fine Art
- Gallery Wraps

IDEAL STORAGE CONDITIONS

70° F (21° C), 50% R.H.; Store in original packaging; A controlled environment is recommended.

SHELF LIFE

Greater than 1 year from the LexJet ship date when stored in proper conditions.

SKU	PRODUCT SIZE
Q GK54150	54" x 150'
Q GK60150	60" x 150'