



DreamGUARD Protex3

Clear Liquid Aqueous Topcoat

**Fast air drying roll on application for
textured dreamScape vinyl surfaces**

Application Instructions

Description: DreamGUARD Protex3 is an aqueous coating formulated specifically for dreamScape textured surfaces but also applicable with most other vinyl products printed with non-water sensitive inks. DreamGUARD provides excellent protection against scratches and abrasion. Can be applied with roll-to-roll liquid laminator or before or after installation with a common paint roller.

Directions: MIX CONTENTS WELL. DreamGUARD may be applied with either a roll-to-roll liquid laminator or with a latex paint roller.

LIQUID LAMINATOR: follow manufacturers instructions.

PAINT ROLLER: use a new, good quality low nap latex paint roller and pan. Can be applied either after printing with work lying flat or after installation on a wall or other vertical surface. Make sure work is free of dust, dirt and grease. Application is similar to paint, allow DreamGUARD to coat roller, roll off excess and apply with even pressure. Product will appear milky white on application to aid in even coverage. Avoid drips and excess liquid. DreamGUARD is self-leveling and will evenly coat deep textures. Milky white appearance will dry clear in about 1-2 hours depending on temperature and humidity. Coating is dry when all cloudiness has cleared and the coated surface is completely dry to touch.

Maintain good ventilation in work area.

For skin contact; wash off with warm soap and water. Eye contact; rinse with plenty of water, consult a physician immediately.

CLEANUP: Wash roller and pan in warm soap and water.

COVERAGE: Approximately 800-1200 square feet per gallon. Will vary with heavily textured surfaces and application method.

APPLY WHERE TEMPERATURE IS BETWEEN 65F and 85F.

CAUTION: PROTECT FROM FREEZING

MSDS is available at www.dreamscapedirect.com