



KODAK Premium

Satin Photo Paper, 240gsm

Produce sharp imagery on this economical, resin-coated photo paper

High-quality photo reproductions at an economical price

KODAK Premium Satin Photo Paper, 240gsm, is a low-gloss, resin-coated photo paper with a weight (240 gsm) and thickness (9.5 mil) comparable to other popular inkjet photo papers, offered at an affordable price designed for all of your photo paper needs.

Wide color gamut and high white point

This satin finish has a high white point, producing sharp, detailed imagery with great contrast. The paper is sufficiently water-resistant to avoid damage during everyday use.

FSC®-certified

Meet environmental objectives with this FSC®-certified paper.

FEATURES:

- Economical solution for a variety of photographic applications
- Sharp details, vivid color and consistency
- FSC®-certified
- Compatible with most pigment and dye-based printer brands

APPLICATIONS:

- Photographic prints
- Fine art reproductions
- Posters
- Interior Décor

US Size	Euro Size	Quantity	SKU
24" x 100'	61,0 cm x 30,5 m	1 Roll	KPRMSPP24100
36" x 100'	91,4 cm x 30,5 m	1 Roll	KPRMSPP36100
44" x 100'	111,7 cm x 30,5 m	1 Roll	KPRMSPP44100
60" x 100'	162,5 cm x 30,5 m	1 Roll	KPRMSPP60100



KODAK Premium

Satin Photo Paper, 240gsm

Properties	Specifications
Printer/Ink Compatibility	Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks
Material	Resin-coated (RC) photo paper
Weight (gsm)	240g
Thickness (μ)	9.5 mils / 242 microns
Finish	Satin
Opacity	> 94
CIE Whiteness	> 134
Core Size	3-in Core
Print Sides	One-sided
Environmental	FSC®-certified
Unit	1 Roll
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Finishing/Post Processing	Pressure-sensitive vinyl laminates with UV inhibitors can be applied to increase the fade and abrasion resistance of the image. Before applying the laminate, allow the image to dry for 24 hours. Residual solvent trapped beneath a laminate as a result of insufficient dry time can cause color shifts
Software Settings	The coating on this product is engineered for better than 300% ink coverage. A photo luster, satin or semi-gloss setting is the recommended starting point. However, we recommend a custom ICC profile for optimal results. Please refer to www.lexjet.com for starting-point ICC profiles for some printers.
Optimal Print Environment	70° F (21° C), 50% R.H
Handling Recommendations	Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet-coated materials. Rolls of LexJet film are supplied with the coated side facing out.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.

BMG BRANDmanagementGROUP

AMS: 888-893-4668
EMEA: +34 935 479 700
APJ: +61 2 8038 5013

KODAKWFMedia.com



The KODAK trademark, logo, and trade dress are used under license from KODAK.

© 2023, Brand Management Group

