



LexJet's 9.5 mil Premium Satin Photo Paper is a low-gloss, resin-coated photo paper with a weight (240 gsm) and thickness (9.5 mil) comparable to other popular inkjet photo papers. LexJet 9.5 mil Premium Satin Photo Paper was designed for all of your Photo Paper needs. The paper is sufficiently water-resistant to avoid damage during everyday use. Plus, this product features a wide color gamut and high white point for greater contrast. This product is FSC® - Certified Paper.

LexJet 9.5 mil Premium Satin Photo Paper can be used on many pigment and dye ink printers from Canon, Epson, and HP, and is engineered for the latest inksets, including Canon Lucia Pro, Epson UltraChrome K3 HDR and HP Vivera.

- Color profiles are available for many models.
- All rolls require a 3-in. spindle or core adapter.

Features	Strengths	Applications
Satin, low-glare finish		Photo reproduction
9.5 mil, 240 gram photo paper		Posters
New and improved inkjet coating with wider color gamut		

Property	Description
Unit	1 Roll
Core Size	3-in
Material	Resin-coated (RC) photo paper
Gauge	9.5 mils
Basis Weight	240g
Whitness	>145 CIE
Opacity	>86%
Surface Finish	Satin
Printer/Ink Compatibility	Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks.
Imaging Side	Material is packaged with printable side facing up. Printable surface can be identified by a slight tackiness.



Property	Description
Finishing/Post Processing	Pressure-sensitive vinyl laminates like LexJet's GraphicsGuard with UV inhibitors can be applied to increase the fade and abrasion resistance of the image. Before applying the laminate, allow the image to dry for 24 hours. Residual solvent trapped beneath a laminate as a result of insufficient dry time can cause color shifts.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Optimal Print Environment	70° F (21° C), 50% R.H
Optimal Service Environment	For printing: 60° - 80° F, 50% Relative Humidity.
Handling Recommendations	Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials. Rolls of LexJet film are supplied with the coated side facing out.
Service Temp. Range	-40° - 176° F (-40° C to 80° C).
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the LexJet ship date when stored in proper conditions.

Size	SKU
36in x 200ft	8PSPSUV36
54in x 200ft	8PSPSUV54
61in x 200ft	8PSPSUV61



The mark of responsible forestry

Note:

The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire cognitions. Consult an architect or fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.