



LexJet's Premium Matte Paper bridges the gap between presentation paper and photo paper. It provides the high ink-load retention needed for saturated colors, quality images, and brilliant colors. Yet this fast-drying paper also works well with thermal laminating films, making this paper ideal for producing high-impact graphics that will be laminated. It is often used by shops who want a low-cost way to produce high volumes of POP displays. This product is FSC® - Certified Paper.

LexJet Premium Matte Paper works with dye or pigment inks and thermal and piezo printheads.

Features	Strengths	Applications
Ideal for high-impact graphics that require thermal laminating.		Posters
Supports highly saturated colors, good image quality, and brilliant colors.		Point-of-purchase graphics
Fast-drying paper that bridges the gap between presentation bonds and photo papers.		Legal graphics

Property	Description
Unit	1 Roll
Core Size	3-in
Material	Matte Coated Paper
Whitness	>150 CIE
Printer/Ink Compatibility	Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks.
Software Settings	For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and color matching software. However, the bond or uncoated paper setting in most RIPs is appropriate. However, we recommend that you try a few different settings to achieve optimum performance for your specific application.



Property	Description
Finishing/Post Processing	It is always recommended that a protective laminate be applied after printing. Thermal or pressure sensitive laminates can be used on bond paper. Before applying the laminate, allow the image to dry for 24 hours.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Please consult with your ink manufacturer for light fastness data.
Optimal Service Environment	For printing: 60-80° F, 50% Relative Humidity.
Handling Recommendations	Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials. Rolls of LexJet film are supplied with the coated side facing out.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the LexJet ship date when stored in proper conditions.

Size	SKU	UPC
24in x 100ft	PRM2410	
24in x 200ft	PRM2420	848412003130
36in x 100ft	PRM3610	848412003147
42in x 100ft	PRM4210	848412003154
50in x 100ft	PRM5010	848412003161
60in x 100ft	PRM6010	848412003178



The mark of responsible forestry

Note:

The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire cognitions. Consult an architect or fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.