



Elevate your work and produce fine-art image quality at an economical price point with Sunset Photo Matte Paper 280g. Print poster decor, fine art reproductions, high-quality fine photo prints and photo albums with this smooth, acid-free, pH-neutral archival paper.

Sunset Photo Matte Paper 280g is the heaviest, thickest paper in its class, weighing in at 280g with a 12-mil thickness. Your clients will appreciate the additional durability, as well as the exceptional bright white point that yields superior color saturation and a high Dmax. This product is FSC® - Certified Paper.

- Thick, heavy and durable: 280g, 12 mil inkjet paper
- Provides application versatility with a fine-art look and feel
- Smooth surface that's acid-free, pH-neutral and archival

| Features | Strengths | Applications |
|--|-----------------------|--------------------------|
| Smooth surface that preserves more details | Smooth, matte surface | Professional Photography |
| Provides application versatility with a fine-art look and feel | pH-neutral | Fine Art Reproduction |
| Thick, heavy and durable | 12 mil & 280g | Décor |

| Property | Description |
|---------------------------|---|
| Unit | 1 Roll |
| Core Size | 3-in |
| Gauge | 12 mils |
| Paper Weight | 280g |
| Printer/Ink Compatibility | Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks. |
| Imaging Side | Material is packaged with printable side facing up. |
| Light Fastness | The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data. |
| Optimal Print Environment | 70° F (21° C), 50% R.H |



| Property | Description |
|-----------------------------|---|
| Optimal Service Environment | For printing: 60° - 80° F, 50% Relative Humidity. |
| Handling Recommendations | Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials. Rolls of LexJet film are supplied with the coated side facing out. |
| Ideal Storage Conditions | 70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging. |
| Shelf Life | 1 year from the LexJet ship date when stored in proper conditions. |

| Size | SKU |
|------------------|--------|
| 24 in. x 100 ft. | SM2400 |
| 36 in. x 100 ft. | SM3600 |
| 44 in. x 100 ft. | SM4400 |
| 60 in. x 100 ft. | SM6000 |



The mark of responsible forestry

Note:
 The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire cognitions. Consult an architect or fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.