

# ELEMENTS

## DECIDUOUS

### Willow

Elements Willow Wallcovering has a classic, smooth finish that's ideal for any setting and installs easily with traditional adhesives and installation techniques. Print colorful, high-definition wall décor with this smooth, matte wallcovering. It is compatible with Latex, Eco-solvent, Solvent, and UV inks.

This commercial-grade wallcovering is **Type II certified**, durable for commercial environments, and environmentally safe for the most sensitive spaces such as schools, hospitals, and public buildings. Elements Willow Wallcovering is a **phthalate-free** PVC substrate.



#### INK COMPATIBILITY

Compatible with Solvent, Eco-solvent, UV curable, and Latex.

#### FIRE HAZARD CLASSIFICATION

This wallcovering passes the National Fire Protection Association NFPA286 Corner Burn Test. Tested in accordance with ASTM E-84 TUNNEL TEST. EN13501 (B-s1,d0).

#### SUSTAINABILITY

Laminated using a water based adhesive to a Low VOC plasticized PVC sheet. PROP 65 compliant.

#### OPTIMAL PRINT ENVIRONMENT

66-77° F, 20-60% Relative Humidity. For end use: 0-300° F.

#### ANTI-MICROBIAL FEATURES

Vinyl wallcoverings contain bactericides and mildew inhibitors to discourage the growth of mold and mildew under normal conditions. Passes ASTM-G21-09.

#### PRODUCT SPECIFICATIONS

BASIS WEIGHT	619 GSM / 20.0 OZ
TEXTURE	SMOOTH
MEDIA OPACITY	OPAQUE
MEDIA TYPE	WALLCOVERING
MATERIAL	FACE MATERIAL PVC
BACKSIDE FABRIC	NON-WOVEN
BRIGHTNESS	>83
WHITENESS	>84
OPACITY	100%
L*a*b* Color Space	L* = 93.04 a* = 0.27 b* = 1.42

#### CLASS A FIRE RATED

FLAME SPREAD 25  
SMOKE DEVELOPED 20  
EN13501 (B-s1,d0)

#### KEY APPLICATIONS

- Soft Signage
- Wall Murals
- Gallery Wraps

#### IDEAL STORAGE CONDITIONS

70° F (21° C), 50% R.H.; Store in original packaging; A controlled environment is recommended.

#### SHELF LIFE

Greater than 1 year from the LexJet ship date when stored in proper conditions.

SKU	PRODUCT SIZE
DOW54150	Elements Willow Wallcovering - 54 in. x 150 ft.
DOW54300	Elements Willow Wallcovering - 54 in. x 300 ft.