




# HP PVC-free Wall Paper



## The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



## Differentiate with PVC-free<sup>1</sup> wall murals

### Designed with the environment in mind

Offer odorless displays that are UL GREENGUARD GOLD Certified<sup>2</sup> and meet AgBB criteria<sup>3</sup> using this FSC®-certified paper.<sup>4</sup>

### Be productive—easy to print, install, and remove

Maintain high productivity in your print shop and offer your customers an easy-to-use solution. This wall paper goes up—and comes down—with water, and it comes with an HP warranty.

### Boldly define interior spaces—see the ColorPRO difference

See high-impact graphics with an extended range of colors. Engineered with ColorPRO Technology to deliver color excellence, this digital wall mural solution from HP delivers professional quality and striking results.

Target customers	Applications	Benefits
Print service providers	Wall murals	PVC-free <sup>1</sup> alternative, easier to dispose of than most PVC-based substrates
	Creative design applications	Mold and mildew resistant <sup>5</sup>
		Vivid color, high-definition detail
		Ultra-smooth finish
		Prepaste facilitates easy application
		Strippable and easy to remove, with an HP warranty
		Flame resistant <sup>6</sup>
		Carries the CE mark <sup>7</sup> and is UKCA compliant <sup>8</sup>
		FSC®-certified paper <sup>4</sup>

## Technical specifications




### HP PVC-free Wall Paper

For the latest ICC profiles/paper presets, please visit [HPLFMedia.com/hp/paperpresets](https://HPLFMedia.com/hp/paperpresets).

<b>Ink compatibility</b>	Original HP Latex Inks																
<b>Weight</b>	175 g/m <sup>2</sup> per ISO 536 Test Method																
<b>Thickness</b>	177 microns/7 mil per ISO 534 Test Method																
<b>Opacity</b>	94% per TAPPI T-425 Test Method																
<b>Brightness</b>	83 per ISO 2470 Test Method																
<b>Whiteness</b>	85 per ISO 11475 Test Method																
<b>Finish</b>	Matte																
<b>Operating temperature</b>	15 to 30° C / 59 to 86° F																
<b>Operating humidity</b>	15 to 80% RH																
<b>Display permanence (Commercial in-window)</b>	Up to 3 years, unlaminated with HP Latex Inks <sup>9</sup>																
<b>Water resistance</b>	Water resistant with HP Latex Inks <sup>10</sup>																
<b>Flame resistance</b>	Class A, B1, EN 13501, M1, and ISO 5660-1:2002 approved fire certifications <sup>6</sup>																
<b>Shelf life</b>	1 year, unopened in original packaging																
<b>Storage temperature</b>	15 to 30° C / 59 to 86° F																
<b>Storage humidity</b>	15 to 80% RH																
<b>Environmental</b>	FSC®-certified paper <sup>4</sup>																
<b>Country of origin</b>	Product of United States																
<b>Ordering information</b>	<table border="1"> <thead> <tr> <th>Product numbers</th> <th>Roll sizes</th> <th>UPC codes</th> <th>Region</th> </tr> </thead> <tbody> <tr> <td>CH098B</td> <td>1067 mm x 30,5 m (42 in x 100 ft)</td> <td>848412009699</td> <td>Worldwide</td> </tr> <tr> <td>CH003B</td> <td>1372 mm x 30,5 m (54 in x 100 ft)</td> <td>848412009675</td> <td>Worldwide</td> </tr> <tr> <td>CH103A</td> <td>1372 mm x 91,4 m (54 in x 300 ft)</td> <td>848412009682</td> <td>Worldwide</td> </tr> </tbody> </table>	Product numbers	Roll sizes	UPC codes	Region	CH098B	1067 mm x 30,5 m (42 in x 100 ft)	848412009699	Worldwide	CH003B	1372 mm x 30,5 m (54 in x 100 ft)	848412009675	Worldwide	CH103A	1372 mm x 91,4 m (54 in x 300 ft)	848412009682	Worldwide
Product numbers	Roll sizes	UPC codes	Region														
CH098B	1067 mm x 30,5 m (42 in x 100 ft)	848412009699	Worldwide														
CH003B	1372 mm x 30,5 m (54 in x 100 ft)	848412009675	Worldwide														
CH103A	1372 mm x 91,4 m (54 in x 300 ft)	848412009682	Worldwide														

<b>Warranty</b>	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see <a href="https://HPLFMedia.com/mediawarranties">HPLFMedia.com/mediawarranties</a> . To obtain warranty service, please contact Brand Management Group customer support at <a href="https://HPLFMedia.com/hp/en/contactus">HPLFMedia.com/hp/en/contactus</a> .
-----------------	--

- Based on HP internal and third-party testing chemical analysis that demonstrates elemental chlorine to be at or below 200 ppm. Presence of chlorine is attributed to residual chlorine used in paper-making process, and not due to the presence of PVC.
- HP PVC-free Wall Paper printed with HP Latex Inks is UL GREENGUARD GOLD Certified. UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit [ul.com/gg-or-green-guard.org](https://ul.com/gg-or-green-guard.org).
- HP PVC-free Wall Paper printed with HP Latex Inks meets AgBB criteria for health-related evaluation of VOC emissions of indoor building products. See [umweltbundesamt.de/en/topics/health/commissions-working-groups/committeefor-health-related-evaluation-of-building](https://umweltbundesamt.de/en/topics/health/commissions-working-groups/committeefor-health-related-evaluation-of-building).
- HP has a policy for offering Forest Stewardship Council® (FSC®)-certified papers that are sourced from FSC®-certified forests and other controlled sources. BMG trademark license code FSC®-C115319, see [fsc.org](https://fsc.org). HP trademark license code FSC®-C017543, see [fsc.org](https://fsc.org). Not all FSC®-certified products are available in all regions. For information about HP large format printing materials, please visit [HPLFMedia.com](https://HPLFMedia.com).
- With HP Latex Inks, UL GREENGUARD found HP PVC-free Wall Paper, which is designed with a breathable construction, to be mold and mildew resistant using test method GGTM.P040 and following the guidelines of ASTM D 6329. See [green-guard.org/en/CertificationPrograms/listingprograms\\_copy1/CertificationPrograms\\_microbialProgram.aspx](https://green-guard.org/en/CertificationPrograms/listingprograms_copy1/CertificationPrograms_microbialProgram.aspx). No products are mold proof. It is uncertain that any material will resist mold or mildew indefinitely.
- Class A, B1, EN 13501, M1, and ISO 5660-1:2002 approved fire certifications.
- Self-declared according to European Standard EN15102.
- Self-declared according to European Standard EN15102 and UKCA.
- Interior in-window display ratings by HP Image Permanence Lab on a range of media. HP predictions based on test data under Xenon-Arc illuminant-calculation assumes 6,000 Lux/12 hrs day. For more information, see [HPLFMedia.com/t/perintpermanence](https://HPLFMedia.com/t/perintpermanence).
- Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see [HPLFMedia.com/t/perintpermanence](https://HPLFMedia.com/t/perintpermanence).



For detailed information on the HP large format printing materials portfolio and to order, visit [HPLFMedia.com](https://HPLFMedia.com)

© 2024 HP Development Company, L.P. © 2024 Brand Management Group. The information contained herein is subject to change without notice.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of HP Development Company, L.P. and is used by Brand Management Group under license from HP Development Company, L.P.

