## **Product Bulletin**

## Concept® 103 TEXTURED OVERLAMINATING FILM

Concept® Textured Overlaminating Film is a pressure sensitive 5.0 mil velvet/very fine matte polycarbonate film with the optically clear RD-60A, permanent acrylic adhesive on a 1.5 mil polyester film liner. This polycarbonate film offers protection from abrasion, moisture and other environmental exposures. It is laminated by the cold laminating process without the addition of heat.

**Applications** Textured overlaminating film is designed to protect digital image prints and screen-

printed images for exhibit and display graphics. Can be used in most instances where an overlay with non-glare properties is required. This film can be used to produce flat,

curved or rolled display graphics.

**Thickness** Film 5.0 mils.

Adhesive 1.4 to 1.6 mils. Liner 1.5 mils. (Thickness variance +/- 10%)

Dimensional Stability Good.

**Temperature Ranges** Minimum application temperature +40° F

Service temperature range -40°F to +200°F.

**Adhesion** To stainless steel 40 oz/in.

When tested according to PSTC-1 with

24 hr. dwell at 70°F and 50% relative humidity.

Typical values. Individual values may vary. Test thoroughly before production.

**Light Transmission** Approximately 84% @ 550nms.

Gloss

**60 ° Gardner** Approximately 19.2.

**Storage Stability** 1-year shelf life when stored at 70°F and 50% relative humidity.

Product Series Concept® #103



Manufacturer of Pressure Sensitive Films, Traffic Graffic Floor Advertising Films, Custom Coatings and Printing Inks.

309 S. Union ● P.O. Box 158 ● Sparta, Michigan 49345 ● (616) 887-7387 ● (800)253-3664 ● FAX (616)887-0537 Web Site: <a href="mailto:www.generalformulations.com">www.generalformulations.com</a> ● e-mail: <a href="mailto:gfiinfo@generalformulations.com">gfiinfo@generalformulations.com</a>