

Product Bulletin

Concept[®] 228

TransMark[®] - 6.0 mil Translucent Vinyl REMOVABLE ADHESIVE

Concept[®] 228 is a 6.0-mil premium translucent calendered PVC film coated with clear 200-4999 removable acrylic pressure sensitive adhesive laminated to a 90# layflat liner. This vinyl film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format digital printing systems. Concept[®] 228 may be printed using other common printing processes such as UV curable screen and UV curable offset but must be tested before production.

Applications

Concept[®] 228 is premium pressure sensitive decal film with uniform light diffusion properties used to produce backlit displays for applications such as taxi tops, backlit bus displays and any other application requiring back lighting. Concept[®] 228 offers excellent bond to substrates such as polycarbonate, styrene and acrylic sheeting while maintaining easy installation and removal properties. CBS Outdoor and Clear Channel taxi top approved displays.

Thickness

Film	6.0 mils.
Adhesive	.8 to 1.1 mils.
Liner	6.7 mils.
(Thickness variance +/- 10%)	

Dimensional Stability

Good.

Temperature Ranges

Minimum application temperature is +40°F.
Service temperature is -40°F to +180°F.

Expected Exterior Exposure

Removable for up to 1 year.

Adhesion

To stainless steel 16 oz/in.
PSTC-101 Method A with 24 hr. dwell at 70°F and 50% relative humidity.
Typical values. Individual values may vary. Test thoroughly before production.

Water Resistance

Excellent

Humidity Resistance

Excellent.

Solvent Resistance

Excellent

Storage Stability

One year shelf life when stored at 70°F and 50% relative humidity.

Product Codes

228-54	(54" X 150' roll)
228-60	(60" X 150' roll)

Recommendations

Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in vinyl degradation. Always thoroughly test this product to confirm it meets your requirements.



**Manufacturer of Pressure Sensitive Films,
Traffic Graffic Floor Advertising Films,
Custom Coatings and Printing Inks.**

Web Site: www.generalformulations.com •

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.