




# HP Professional Gloss Photo Paper



## The HP large format printing system—the complete solution

HP Latex printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



## Experience outstanding, heavyweight, resin-coated photo paper for photographic printing

### Enjoy high-performance photo printing

Now you can print high-end photography, posters, and retail graphics for either custom or high-volume projects with your HP Latex printer on this versatile resin-coated photo paper.

### Move quickly and efficiently through production

There's no need to wait; print and deliver to provide quick turnarounds for your customers. This heavyweight photo paper (275 g/m<sup>2</sup>) also provides increased stability for handling high-volume production.

### Achieve spot-on, dynamic color

The bright-white finish provides a high dynamic range and a wide color gamut for color-critical, eye-catching reproductions on a gloss finish.

<sup>1</sup> BMG trademark license code FSC®-C115319, see [fsc.org](http://fsc.org).  
 HP trademark license code FSC®-C017543, see [fsc.org](http://fsc.org).  
 Not all FSC®-certified products are available in all regions.

Target customers	Applications	Benefits
Point-of-purchase providers	Photo enlargements	Prints come out completely dry, enabling production printing
Trade show and exhibit companies	Art and décor reproductions	Heavy, thick construction for easy handling
Photo and art reproduction houses	Point-of-purchase displays	Wide color gamut and bright-white surface
	Trade show and event displays	FSC-certified paper <sup>1</sup>

## Technical specifications



### HP Professional Gloss Photo Paper

For the latest ICC profiles/paper presets and a variety of resources to help you get the most out of your printer and HP large format printing materials, please visit [globalBMG.com/hp](http://globalBMG.com/hp).

<b>Weight</b>	275 g/m <sup>2</sup> per ISO 536 Test Method			
<b>Thickness</b>	248 microns/9.8 mil per ISO 534 Test Method			
<b>Opacity</b>	Greater than 96% per TAPPI T-425 Test Method			
<b>Brightness</b>	96% per TAPPI T-452 Test Method			
<b>Whiteness</b>	130 per ISO 11475 Test Method			
<b>Finish</b>	Gloss			
<b>Operating temperature</b>	15 to 35° C / 59 to 95° F			
<b>Operating humidity</b>	30 to 80% RH			
<b>Dry time</b>	Instant dry			
<b>Shelf life</b>	1 year, unopened in original packaging			
<b>Storage temperature</b>	0 to 40° C / 32 to 104° F			
<b>Storage humidity</b>	5 to 95% RH			
<b>Country of origin</b>	Product of Germany			
<b>Ordering information</b>	<b>Product numbers</b>	<b>Roll sizes</b>	<b>UPC codes</b>	<b>Region</b>
	E4J42A	914 mm x 30,5 m (36 in x 100 ft)	848412014464	Worldwide
	E4J43A	1067 mm x 30,5 m (42 in x 100 ft)	848412014471	Worldwide
	E4J44A	1372 mm x 30,5 m (54 in x 100 ft)	848412014488	Worldwide
	E4J45A	1524 mm x 30,5 m (60 in x 100 ft)	848412014495	Worldwide
<b>Warranty</b>	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see <a href="http://globalBMG.com/hp/mediawarranties">globalBMG.com/hp/mediawarranties</a> .			



Note: Not all FSC®-certified products are available in all regions.

For detailed information on the HP large format printing materials portfolio and to order, see [globalBMG.com/hp](http://globalBMG.com/hp)

