




# HP Super Heavyweight Plus Matte Paper, 3-in Core

This product is only compatible with HP Latex Printers



## The HP large format printing system—the complete solution

HP Designjet, HP Latex, and HP Scitex Printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



## Produce professional full-color graphics

### See highly saturated images that lie flat, smooth

When the job requires professional full-color graphics and photo-realistic images this heavy, matte-finish paper—with a barrier layer under a thick top coating that enables ripple-free prints—delivers excellent highlights and rich shadow details.

### Streamline your workflow

Move quickly and smoothly through post-print processing. Instant-dry, smear-resistant prints—even with high ink densities—enable immediate handling and lamination. Excellent film laminate compatibility helps you keep peak productivity.

### Create a versatile set of jobs

A wide array of graphics-display applications with this recyclable paper.

Target customers	Applications	Benefits
Print service providers	Tradeshows and event displays	Highly-saturated, photo-realistic images
Large retailers	Posters and presentations	Bright white, smooth coating for vivid color contrast
Graphic designers	POP and retail displays	Flat, smooth prints even under high ink densities
Ad agencies	Geographic Information Systems (GIS)	Excellent film laminate compatibility
Repro houses	Architecture (AEC)	Instant-dry, smear-resistant prints
Geographic Information Systems (GIS) professionals	Engineering (CAD)	
Architects		

## Technical specifications



### HP Super Heavyweight Plus Matte Paper, 3-in Core

For the latest ICC profiles/paper presets, please visit [globalBMG.com/hp/paperpresets](http://globalBMG.com/hp/paperpresets).

<b>Weight (without liner)</b>	210 g/m <sup>2</sup> per ISO 536 Test Method, (55 lbs)			
<b>Thickness</b>	259microns /10.2 mil per ISO 534 Test Method			
<b>Opacity</b>	98% per TAPPI T-425 Test Method			
<b>Brightness</b>	91% per TAPPI T-452 Test Method			
<b>Whiteness</b>	130 per CIE Ganz 82 Test Method			
<b>Finish</b>	Matte			
<b>Operating temperature</b>	15 to 35° C / 59 to 95° F			
<b>Operating humidity</b>	20 to 80% RH			
<b>Dry time</b>	Instant dry (at 23° C, 50% RH)			
<b>Lamination</b>	Yes, compatible with thermal, heat assist, and pressure-sensitive film laminates			
<b>Shelf life</b>	1 year, unopened in original packaging			
<b>Storage temperature</b>	0 to 40° C / 32 to 104° F			
<b>Storage humidity</b>	5 to 95% RH			
<b>Recyclability</b>	Recyclable through commonly available recycling programs			
<b>Country of origin</b>	Product of Switzerland			
<b>Ordering information</b>	<b>Product numbers</b>	<b>Roll sizes</b>	<b>UPC codes</b>	<b>Region</b>
	D9R36A	914 mm x 61 m (36 in x 200 ft)	848412010022	North America, Europe, Asia
	D9R37A	1067 mm x 61 m (42 in x 200 ft)	848412010039	North America, Europe, Asia
	D9R38A	1270 mm x 61 m (50 in x 200 ft)	848412010046	North America, Europe, Asia
	D9R39A	1524 mm x 61 m (60 in x 200 ft)	848412010053	North America, Europe, Asia
<b>Warranty</b>	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see <a href="http://globalBMG.com/hp/mediawarranties">globalBMG.com/hp/mediawarranties</a> .			



**For information about HP Sign and Display Printing Materials for HP Latex and UV printers, please visit [globalBMG.com/hp/signagemedia](http://globalBMG.com/hp/signagemedia)**

**For information about HP Graphics and Technical Printing Materials for HP Designjet T & Z series printers, please visit [hp.com/go/LFPrintingMaterials](http://hp.com/go/LFPrintingMaterials)**

