

HP Heavyweight Coated Paper / 35

print quality	
brightness	heavyweight coated paper, 60 in/ heavyweight coated paper, 24 in/ heavyweight coated paper, 36 in/ heavyweight coated paper, 42 in/ heavyweight coated paper, 54 in: >90 per TAPPI T-452 Test Method heavyweight coated paper, 42 in/ heavyweight coated paper, 60 in: 90 per TAPPI T-452 Test Method
weight, printing material	35 lb
dry time	Immediate
gloss level	Not applicable
lamination	heavyweight coated paper, 60 in/ heavyweight coated paper, 24 in/ heavyweight coated paper, 36 in/ heavyweight coated paper, 42 in/ heavyweight coated paper, 54 in: Yes/Hot heavyweight coated paper, 42 in/ heavyweight coated paper, 60 in: Yes
lightfastness	Delta E<12 (3 months indoors)
opacity	heavyweight coated paper, 60 in/ heavyweight coated paper, 24 in/ heavyweight coated paper, 36 in/ heavyweight coated paper, 42 in/ heavyweight coated paper, 54 in: >93 per TAPPI T-425 Test Method heavyweight coated paper, 42 in/ heavyweight coated paper, 60 in: 93 per TAPPI T-425 Test Method
shelf life	heavyweight coated paper, 60 in/ heavyweight coated paper, 24 in/ heavyweight coated paper, 36 in/ heavyweight coated paper, 42 in/ heavyweight coated paper, 54 in: One year heavyweight coated paper, 42 in/ heavyweight coated paper, 60 in: 2 years
smoothness	heavyweight coated paper, 60 in/ heavyweight coated paper, 24 in/ heavyweight coated paper, 36 in/ heavyweight coated paper, 42 in/ heavyweight coated paper, 54 in: 165 SU heavyweight coated paper, 42 in/ heavyweight coated paper, 60 in: 147 per TAPPI T-538 Test Method
thickness / caliper	heavyweight coated paper, 60 in/ heavyweight coated paper, 24 in/ heavyweight coated paper, 36 in/ heavyweight coated paper, 42 in/ heavyweight coated paper, 54 in: 6 mil/153 μ heavyweight coated paper, 42 in/ heavyweight coated paper, 60 in: 6.4 mil/163 μ
waterfastness	heavyweight coated paper, 60 in: Delta OD<0.11 heavyweight coated paper, 24 in/ heavyweight coated paper, 36 in/ heavyweight coated paper, 42 in/ heavyweight coated paper, 54 in: Delta OD<0.10
compatibility	
compatibility	heavyweight coated paper, 60 in/ heavyweight coated paper, 24 in/ heavyweight coated paper, 36 in/ heavyweight coated paper, 42 in/ heavyweight coated paper, 54 in: HP Designjet 300 series, 400 series, 500 series, 700 series, 800 series, 1000 series, 2000 series, 3000 series and 5000 series printers

	heavyweight coated paper, 42 in/ heavyweight coated paper, 60 in: HP Designjet 5000 Series printers
warranty	
warranty, std.	90 day warranty, manufacturer will replace if defective
environmental specifications	
operating humidity	heavyweight coated paper, 60 in/ heavyweight coated paper, 24 in/ heavyweight coated paper, 36 in/ heavyweight coated paper, 42 in: 20 to 80% RH heavyweight coated paper, 42 in/ heavyweight coated paper, 60 in: 20% to 80% RH
storage humidity	heavyweight coated paper, 60 in/ heavyweight coated paper, 24 in/ heavyweight coated paper, 36 in/ heavyweight coated paper, 42 in: 0 to 95% RH heavyweight coated paper, 42 in/ heavyweight coated paper, 60 in: '5% to 95% RH
storage temperature range, fahrenheit	heavyweight coated paper, 60 in/ heavyweight coated paper, 24 in/ heavyweight coated paper, 36 in/ heavyweight coated paper, 42 in: 32 to 113° F heavyweight coated paper, 42 in/ heavyweight coated paper, 60 in: 32 to 104° F